

# PAC-5011

## Extended-ITX Embedded Chassis



### Features

- Mini-ITX & IEI extended mini-ITX embedded chassis
- Compatible with IEI proprietary extended mini-ITX SBC (depth +30 mm)
- 2-slot PCI/PCIe half-height, half-length expansion
- Supports 1U FLEX power supply
- Up to 3 x 2.5" internal drive bays
- RoHS compliant design

### Specifications

<b>Construction</b>	Heavy-duty steel, powder-coated
<b>SBC Form Factor</b>	Mini-ITX & IEI extended mini-ITX
<b>Color</b>	Gray, powder-coated
<b>PSU</b>	1U FLEX Power Supply
<b>Drive Bay</b>	3 x 2.5" internal SSD/HDD
<b>Cooling Fan</b>	1 x system fan position (optional)
<b>Expansion Slots</b>	2-slot Half-length, half-height
<b>Indicators</b>	1 x Power LED
<b>Button</b>	Power button, Reset button
<b>Operating Temperature</b>	-10°C ~ 50°C
<b>Operating Humidity</b>	5% ~ 95% (non-condensing)
<b>Operating Shock</b>	Half-sine wave shock 5G, 11ms, 100 shocks per axis
<b>Operation Vibration</b>	MIL-STD-810F 514.5C-1
<b>Weight (Net/Gross)</b>	2.12kg / 3.11kg
<b>Dimensions (DxWxH)(mm)</b>	270.2 x 267.0 x 88.6

### Ordering Information

Part No.	Description
PAC-5011-R10	Extended-ITX two Half-height slot ATX Chassis, 2xUSB2.0, ATX Power Switch, Gray, Powder paint, RoHS

### Packing List

2 x Wall mount bracket
1 x Screw pack

### Optional Accessories

Item	Part No	Description
FAN	31100-000434-RS	FAN;+12V;4PIN;Everflow;60*60*15mm;4200RPM ;TWO BALL BEARING

### Motherboard Options

Model No.	SBC Type	Slot
KINO-ADL-H610	Mini-ITX	1 x PCIe Gen4 x16
KALI-ADL-Q670	Extended-ITX	1 x PCIe Gen4 x16
KALI-C262	Extended-ITX	1 x PCIe Gen4 x16

### Power Supply Options

Type	Model No	Watt
1U Flex	63030-010500-030-RS	500W(FSP)
	63030-010400-010-RS	400W(FSP)
	63030-010300-000-RS	300W(FSP)
	63030-410500-000-RS	500W(LITEON)

### Dimensions (Unit: mm)

