
RACK-500AI

5U 5-slot Full-size Rackmount Chassis



CA-950GB-R10



CA-950GB-R10

19" rack carrier can carry four RACK-500Al and fit into standard 19"-width rack with 5U height.



FDD and HDD are not included in the package

Features

- RoHS compliant design
- 2 x USB ports on front panel
- One front-accessible 3.5" and one internal 3.5" HDD drive bays
- Hot-swappable 8 cm cooling fan
- 19" rack-mountable carrier (optional)

Specifications

◆ Construction	Heavy duty metal			
♦ SBC Form Factor	Full-size CPU cards			
♦ Drive Bays	1 x Front-accessible 3.5" 1 x 3.5" HDD			
♦ Cooling Fans	1 x 8 cm			
♦ I/O Ports	2 x USB			
♦ I/O Openings	1 x LPT, 1 x COM			
♦ Expansion Slots	5 slots			
♦ Indicators	Power, HDD			
♦ Button	Power switch, reset button			
♦ Operating Temperature	0°C ~ 50°C			
♦ Operating Humidity	10% ~ 90%			
♦ Color	Navy blue and black			
♦ Weight (Net/Gross)	6 kg/9 kg			
♦ Dimensions (DxWxH)	440.2 mm x 110.6 mm x 221.3 mm			
◆ PCIe Expansion Card (GPU/Add-on Cards)	Total maximum up to 150W (80W CPU with 16GB memory, 350W ATX Power)			
Recommendation	Total maximum up to 180W (35W CPU with 16GB memory, 350W ATX Power)			


Ordering Information

Part No.	Description
RACK-500AI-R20/FSP350	5U Height 5-Slots Full-size Chassis, Navy Blue and Black, Powder paint, 1x 8cm fan, with FSP350- 50FCB(350W), RoHS

Cable Options

Part No.	Description
32100-126600-RS (2.54mm → 2.0mm)	This optional cable is required for motherboard with 2mm USB connector (the USB cable inside the chassis is with 2.54mm pitch). Refer to motherboard spec. for details.
32102-004600-100-RS	Some full-length CPU card's CPU power connector may be up to 650mm away from the power supply when installed. Select this power adapter cable if the cable of the power supply is not long enough.

Dimensions (Unit: mm)



Backplane Options

	Model No.	SBC Type	PCI ISA		PCle ISA			PSU
'	wioder No.	ово туре	FOI	ISA	x1	x4	x16	Connector
Р	CI-5S2-RS	PICMG 1.0	4	1	0	0	0	AT
PO	CI-5S2A-RS	PICMG 1.0	4	1	0	0	0	ATX
	PE-3S1	PICMG 1.3	0	0	0	1	1	ATX
	PE-5S2	PICMG 1.3	0	0	3	0	1	ATX
	PE-5S	PICMG 1.3	2	0	0	1	1	ATX
	HPE-5S1	PCI/PICOe	4	0	0	0	0	ATX
Н	IPXE2-5S1	HPCIE	2	0	0	0	1	ATX

^{*}Only R20 or later versions support PICMG 1.3 backplane.

Power Supply Options

Туре	Model No.	Watt
ATX	63030-010180-000-RS	180W
	63030-010350-000-RS	350W

RACK-500Al-R10 supports single PS/2 PSU. For more IEI PSU models, please visit www.ieiworld.com.