

PPC2-C15-ADL

IEI Heavy Industrial Panel PC

Powered by Intel® Alder Lake S & Raptor Lake S platform




IEI

WWW.IEIWORLD.COM



PPC2-C15-ADL

Panel PC equips 12/13/14th Gen Intel® Alder Lake S & Raptor Lake S series processor, HDMI 2.0 display output, dual 2.5G Ethernet port, one PCIe Gen4 x16 slot, one M.2 M key & one M.2 E key expansion slots, anti-glare & anti-UV 10-point touchscreen, and IP65 compliant front panel




12/13/14th Gen Intel® Desktop Platform

Support 12/13/14th Gen Intel® Core™/Pentium® series desktop processor, and asynchronous architecture to unleash superb performance



PCIe Gen4 x16 (x16 signal) Slot

One PCIe x16 for functional expansions like graphics cards, LAN cards or motion control cards.



Anti-glare and Anti-UV PCAP

With anti-glare and anti-UV coating, the 10-point touchscreen can display clearly without reflection.



Support Gloved and Wet Hand Operation

The whole new PCAP screen allows you to accurately manage every step of your operations even with gloves or in wet conditions.




Newly Designed Panel Mount Kit

The new refined and convenient panel mount kit can be easily fastened by hand, no screwdriver required.




New Graphical BIOS Interface

Upgraded with new BIOS interface, which can be navigated with fingers, no keyboard and mouse are required to operate.




PPC2-C15-ADL I/O




PPC2-C15-ADL Block Diagram

PPC2-C15-ADL Block Diagram



Dimensions



Specifications

Model	PPC2-C15-ADL	
LCD Display	15" (4:3)	
Resolution	1024 (W) x 768 (H)	
Brightness	400 cd/m ²	
Contrast Ratio	800:1	
LCD Color	16.2M	
Pixel Pitch (mm)	0.297 x 0.297	
Viewing Angle (H-V)	160°/150°	
Backlight MTBF	70,000 hours	
CPU	Support 12/13/14th Gen Intel® Core™ i9/i7/i5/i3 and Pentium® Processor	
Chipset	Intel® H610	
Graphics Engine	New Intel® Xe Graphics architecture with SRIOV, Genlock	
Display Output	1 x HDMI 2.0	
Memory	2 x SO-DIMM DDR4 3200Mhz (8GB pre-installed) (up to 64GB)	
Touchscreen	Multi-point projected capacitive type	
	Surface hardness: ≥7H	
Touch Controller	Projected capacitive type: EETI EXC80 Series	
Storage	1 x 2.5" SATA HDD bay (Height limit: 7.5mm)	
Ethernet	LAN1: Intel® I225 + LAN2: Intel® I225	
	1 x PCIe Gen4 x 16 slot with x16 Signal	
Expansion	1 x M.2 E-Key 2230 (PCIe Gen3 x1 + CNVio2 + USB 2.0)	
	1 x M.2 M Key 2242/2280 NVMe (PCIe Gen3 x4)	
Mounting	VESA 100 / Panel Mount / Rack Mount	
Construction Material	Aluminum front cover and sheet metal rear cover	
Enclosure Color	Black C	
I/O Ports, Switches and Buttons	1 x HDMI 2.0	4 x RS-232
	2 x 2.5GbE RJ45	1 x AC input
	2 x USB 2.0 (Type-A)	1 x Power switch
	2 x USB 3.2 Gen1 (Type-A) (5Gb/s)	1 x Clear CMOS button
	2 x USB 3.2 Gen2 (Type-A) (10Gb/s)	1 x Reset button
	1 x RS-232/422/485 (RS-485 support AFC)	1 x AT/ATX switch
Power Supply	250W ATX power supply	
	Support AT/ATX mode	
Thermal Solution	Smart fan (2 x CPU fan, 2 x System fan)	
TPM	Intel® Platform Trust Technology	
Watchdog Timer	Software Programmable Support 1~255 sec. system reset	
Operating Temperature (with air flow)	-10°C ~ 60°C	
Storage Temperature	-20°C ~ 60°C	
Humidity	10% to 95% @40°C (non-condensing) (50% @60°C)	
IP Level	IP 65 compliant front panel	
Safety and EMC	CE, FCC Class A, UKCA	
ErP	ErP 2009/125/EC	
Dimensions(H x W x D) (mm)	378.5 x 303 x 76.16	
Cutout Dimensions (mm)	Cutout Dimensions (mm)	
Weight (Net/Gross)	5.7 kg / 9.7 kg	

Packing List

1 x Power Cord	1 x QIG
1 x Panel Mount Kit	1 x Screw Pack

Ordering Information

PPC2-C15-ADL-i7/8G-R10	15" 400 cd/m ² 1024x768 panel PC with 12th Intel® Core™ i7-12700 processor (25M cache, up to 4.90 GHz), TDP 65W, 8GB DDR4, HDMI output, 1 x PCIe Gen4 x16 slot, 1 x M.2 E key, 1 x M.2 M key, ATX/AT power supply, PCAP touchscreen with AG, R10
PPC2-C15-ADL-i5/8G-R10	15" 400 cd/m ² 1024x768 panel PC with 12th Intel® Core™ i5-12400 processor (25M cache, up to 4.90 GHz), TDP 65W, 8GB DDR4, HDMI output, 1 x PCIe Gen4 x16 slot, 1 x M.2 E key, 1 x M.2 M key, ATX/AT power supply, PCAP touchscreen with AG, R10
PPC2-C15-ADL-i3/8G-R10	15" 400 cd/m ² 1024x768 panel PC with 12th Intel® Core™ i3-12100 processor (12M cache, up to 4.30 GHz), TDP 60W, 8GB DDR4, HDMI output, 1 x PCIe Gen4 x16 slot, 1 x M.2 E key, 1 x M.2 M key, ATX/AT power supply, PCAP touchscreen with AG, R10
PPC2-C15-ADL-P/8G-R10	15" 400 cd/m ² 1024x768 panel PC with 12th Intel® Pentium® Gold G7400 processor (6M cache, 3.70 GHz), TDP 46W, 8GB DDR4, HDMI output, 1 x PCIe Gen4 x16 slot, 1 x M.2 E key, 1 x M.2 M key, ATX/AT power supply, PCAP touchscreen with AG, R10

Options

Item	Part No.	Description
Rack Mount	FRK15-PPC2-R10	15" 4:3 monitor rack mount kit, blackQ
Stand	STAND-C19-R10	VESA 75/100 easy stand
Wall	AFLWK-19B	Wall mounting kit
OS	PPC2-ADL-S-W110t24-V-R10	OS Image with Windows® 11 Enterprise Value 64-bit 2024 LTSC for PPC2-ADL-S i3 & i5 Series
	PPC2-ADL-S-W110t24-H-R10	OS Image with Windows® 11 Enterprise High End 64-bit 2024 LTSC for PPC2-ADL-S i7 Series
	PPC2-ADL-S-W100t21-V-R11	OS Image with Windows® 10 Enterprise Value 64-bit 2021 LTSC for PPC2-ADL-S i3 & i5 Series
	PPC2-ADL-S-W100t21-H-R11	OS Image with Windows® 10 Enterprise High End 64-bit 2021 LTSC for PPC2-ADL-S i7 Series
Wi-Fi Kit	EMB-WIFI-KIT02i3-R10	2T2R M.2 Wi-Fi module, Wi-Fi 6E & Bluetooth 5.2