

63010-411200-000-RS

1200W PS/2 ATX POWER
SUPPLY

Ordering Information

Part No.	Description
63010-411200-000-RS	1200W PS/2 ATX POWER SUPPLY,ROHS

Specifications

Input	Voltage	90~264 VAC Full Range		
	Frequency	47 Hz ~ 63 Hz		
	Input Current	15A (RMS)@132VAC, 7A (RMS)@264VAC		
	Inrush Current	≤component rating		
Output	Voltage	Min. load	Max. load	Ripple & Noise
	+3.3V	0 A	20 A	50mV
	+5V	0 A	20 A	50mV
	+12V1	0 A	100 A	120mV
	-12V	0 A	0.3 A	120mV
	+5VSB	0 A	3 A	50mV
Maximum continuous total DC output power should not exceed 1200W. Maximum continuous combined load on 3.3V and 5V outputs shall not exceed 110W. Maximum continuous combined load on 12V output shall not exceed 1200W.				
Over Voltage Protection		+3v: ≤4.6V +5v: ≤6.8V +12v: ≤15.6V +5Vsb: ≤7.5V		
Short Circuit Protection		+3.3v,+5v,+12v,+5vsb,-12v shutdown and latch off		
General Specifications	Watt	1200W		
	PFC	Active		
	Hold-up Time	16 ms min.		
	Efficiency	87%		
	MTBF	700,000 hours		
	Temperature	Operating: 0°C ~ 50°C Storage: -20°C ~ 85°C		
	Dimensions (mm)	140 x 150 x 86		
Output Connector		1 x 20+4-pin ATX, 1 x 8-pin 12V CPU, 8 x HDD/CDROM, 2x Graphics card power, 6 x SATA 1xPCIe5.0		

Dimensions (Unit: mm)

