PCI Express Power over Ethernet card, 4-port 1000 Base(T), 802.3at/af compliant, low profile, RoHS

GPOE-4P

Quick Installation Guide Version 1.0

Aug 29, 2018.

Package List

GPOE-4P package includes the following items:

- 1 x GPOE-4P card
- 1 x QIG (Quick Installation Guide)



Specifications

• Interface: PCI Express® x1

• Ethernet:

Intel® I211AT controller 9kB jumbo frame IEEE 802.3az, IEEE1588

• PWR input:

12~24V DC input

1 x Internal DC input (1x4 pin)

1 x Internal DC input (2x3 pin)

**Caution! Choose one input only at a time

PoE Capability:

Standard mode: IEEE 802.3af with 15.4W / 52V per port Dual port mode: IEEE 802.3at with 30W / 52V per port

Operating Temperature: 0°C ~ 60°C

• Storage Temperature: -10°C ~ 70°C

• Operation Humidity: 5% ~ 95%, non-condensing

• Dimensions: 160 mm x 65 mm

• Weight: 110g

CE/FCC compliant

Ordering Information

• GPOE-4P-R10:

PCI Express Power over Ethernet card, 4-port 1000 Base(T), 802.3af compliant, low profile, RoHS

• <u>32102-045800-100-RS:</u>

WIRE cable, power cable, 2, 300MM, 20AWG, (A) DC JACK 5.5*2.1+NUT+WASHER (Smcts:655-353),

(B) TKP: H6657R1-06-B-03 P=4.2, Polywell, RoHS

Jumpers setting and connectors


LABEL	FUNCTION
CN1	2 X 3 Power In Connector
J2	1 X 4 Power In Connector
PLAN1	1 X 4 RJ45 Connector


CN1: 2 X 3 Power In Connector					
PIN NO.	DESCRIPTION	PIN NO.	DESCRIPTION		
1	Power in	4	GND		
2	Power in	5	GND		
3	Power in	6	GND		

J2: 1 X 4 Power In Connector					
PIN NO.	DESCRIPTION	PIN NO.	DESCRIPTION		
1	Power in	2	GND		
3	GND	4	NC		

PLAN1: 1 X 4 RJ45 Connector					
PIN NO.	DESCRIPTION	PIN NO.	DESCRIPTION		
1	P0	2	N0		
3	P1	4	P2		
5	N2	6	N1		
7	P3	8	N3		

Board Layout: Jumper and Connector Locations







(Unit: mm)