

iM2-DLAN2

Dual 2.5GbE LAN M.2 2280 B+M Key Module

Quick Installation Guide

Version 1.00

June 21, 2024

Features

- M.2 2280 B+M key module supports dual 2.5GbE LAN
- Intel® I226-V Ethernet controllers
- Support link aggregation/jumbo frames (9 Kbyte)

Packing List

- 1 x iM2-DLAN2 module
- 1 x RJ-45 connector card
- 2 x Flat LAN cable (p=1.25mm)
- 1 x I/O shielding
- 1 x QIG (Quick Installation Guide)



Specifications

Form Factor	n Factor M.2 B+M key 2280	
Input Interface	M.2 B/M key 2280 (PCIe Gen3 x2 signal)	
Ethernet Controller	LAN1: Intel® I226-V controller	
	LAN2: Intel® I226-V controller	
Speed	100/1000/2500 Mbps	
External Connector	2 x RJ-45 Ethernet connector (8-pin)	
Internal Connector	2 x 14-pin LAN port	
Operating Temperature	-10°C ~ 60°C	
Storage Temperature	-20°C ~ 70°C	
Operating Humidity	ting Humidity 5% ~ 95%, non-condensing	
Dimensions (WxL)	22 mm x 80 mm	
Safety	CE/FCC compliant	

Connectors


J1/J2: Internal 14-pin LAN connectors (on the iM2-DLAN2)							
Pin	Description	Pin	Description				
1	+3.3V	8	MDI1_N	□ □ 14			
2	INK_ACT_N	9	MDI2_P	14 ahaaaaaaaaaaaaa 199999999999999999999999			
3	1G_N	10	MDI2_N				
4	2.5G_N	11	MDI3_P				
5	MDI0_P	12	MDI3_N				
6	MDI0_N	13	GND	-			
7	MDI1_P	14	GND				

LAN1/LAN2: External RJ-45 LAN connectors (on the RJ-45 connector card)						
Pin	Description	Pin	Description			
1	MDIA0+	2	MDIA0-			
3	MDIA1+	4	MDIA2+			
5	MDIA2-	6	MDIA1-	القمممممما		
7	MDIA3+	8	MDIA3-			




Dimensions (Unit: mm)

iM2-DLAN2 module:



RJ-45 connector card:





Safety Instructions



Warning! Read the user manual before connecting the system to the power source.

Warning! To prevent the system from overheating, do not operate it in an area that exceeds the maximum operating temperature described in the user manual.

Warning! Ultimate disposal of this product should be handled according to all national laws and regulations.

Support



IEI Support URL

http://new.ieiworld.com/tw/online support form

Compliance



This equipment has been tested and found to comply with specifications for CE marking. If the user modifies and/or installs other devices in the equipment, the CE conformity declaration may no longer apply.



This equipment complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- This device may not cause harmful interference, and
- This device must accept any interference received, including interference that may cause undesired
 operation.

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.



According to the requirement of the WEEE legislation the following user information is provided to customers for all branded IEI Electronics products subject to the WEEE directive.

This symbol on the product or on its packaging indicates that this product must not be disposed of with your other household waste. Instead, it is your responsibility to dispose of your waste equipment by handing it over to a designated collection point for the recycling of waste electrical and electronic equipment. The separate collection and recycling of your waste equipment at the time of disposal will help to conserve natural resources and ensure that it is recycled in a manner that protects human health and the environment. For more information about where you can drop o- your waste equipment for recycling, please contact your local city office, your household waste disposal service or the shop where you purchased the product.

Headquarters

IEI Integration Corp.

No. 29, ZhongXing Rd., Xizhi Dist., New Taipei City 221, Taiwan TEL: +886-2-8691-6798/+886-2-2690-2098 FAX: +886-2-6616-0028

sales@ieiworld.com www.ieiworld.com

America

IEI Technology USA Corp.

138 University Parkway, Pomona, CA 91768, USA Tel:+1-909-595-2819 Fax:+1-909-595-2816 sales@usa.ieiworld.com usa.ieiworld.com

China

IEI Integration (Shanghai) Corp.

No. 515, Shen Fu Rd., Xin Zhuang Industrial Develop Zone, Shanghai, 201108, China Tel:+86-21-3116-7799 Fax:+86-21-3462-7797 sales@ieiworld.com.cn www.ieiworld.com.cn