



MODEL:
DRPC-120-BTi

**Fanless Embedded System with Intel® Atom™ E3845 CPU,
DIN Rail Mounting Support, OLED Display or LED Indicators,
Dual GbE, USB, DIO, Serial Ports,
9V~28V DC Power Input, RoHS Compliant**

User Manual

Revision

| Date | Version | Changes |
|-------------------|---------|---|
| March 25, 2015 | 1.01 | Added a warning message in Section 3.3: HDD Installation Added Appendix A: Regulatory Compliance |
| November 20, 2014 | 1.00 | Initial release |

Copyright

COPYRIGHT NOTICE

The information in this document is subject to change without prior notice in order to improve reliability, design and function and does not represent a commitment on the part of the manufacturer.

In no event will the manufacturer be liable for direct, indirect, special, incidental, or consequential damages arising out of the use or inability to use the product or documentation, even if advised of the possibility of such damages.

This document contains proprietary information protected by copyright. All rights are reserved. No part of this manual may be reproduced by any mechanical, electronic, or other means in any form without prior written permission of the manufacturer.

TRADEMARKS

All registered trademarks and product names mentioned herein are used for identification purposes only and may be trademarks and/or registered trademarks of their respective owners.

Table of Contents

| | |
|---|-----------|
| 1 INTRODUCTION..... | 1 |
| 1.1 OVERVIEW..... | 2 |
| 1.2 MODEL VARIATIONS | 2 |
| 1.3 FEATURES..... | 3 |
| 1.4 CONNECTOR PANEL | 4 |
| 1.4.1 <i>Front Panel</i> | 4 |
| 1.4.2 <i>Top Panel</i> | 5 |
| 1.5 LED INDICATORS (DRPC-120-BTi-E5-LED ONLY)..... | 6 |
| 1.6 PROGRAMMABLE OLED DISPLAY (DRPC-120-BTi-E5-OLED ONLY) | 7 |
| 1.7 TECHNICAL SPECIFICATIONS | 7 |
| 1.8 DIMENSIONS..... | 10 |
| 2 UNPACKING | 11 |
| 2.1 ANTI-STATIC PRECAUTIONS | 12 |
| 2.2 UNPACKING PRECAUTIONS..... | 12 |
| 2.3 UNPACKING CHECKLIST | 13 |
| 3 INSTALLATION | 16 |
| 3.1 INSTALLATION PRECAUTIONS | 17 |
| 3.1.1 <i>High Surface Temperature</i> | 17 |
| 3.2 INTERNAL ACCESS PANEL REMOVAL | 18 |
| 3.3 HDD INSTALLATION..... | 19 |
| 3.4 mSATA SSD INSTALLATION..... | 20 |
| 3.5 IPMI MODULE INSTALLATION (OPTIONAL)..... | 22 |
| 3.6 CLEAR CMOS..... | 23 |
| 3.7 AT/ATX MODE SELECTION | 24 |
| 3.8 MOUNTING THE SYSTEM | 24 |
| 3.9 EXTERNAL PERIPHERAL INTERFACE CONNECTORS..... | 26 |
| 3.9.1 <i>Digital Input/Output Terminal Block</i> | 27 |
| 3.9.2 <i>LAN Connectors</i> | 27 |
| 3.9.3 <i>Power Input, 3-pin Terminal Block</i> | 29 |

DRPC-120-BTi Embedded System

| | |
|--|-----------|
| 3.9.4 RS-232 Serial Port Connectors (COM1, COM2) | 30 |
| 3.9.5 RS-422/485 Serial Port Connectors (COM3, COM4) | 31 |
| 3.9.6 USB Connectors | 32 |
| 3.9.7 VGA Connector | 33 |
| 3.10 IPMI SETUP PROCEDURE | 33 |
| 3.10.1 Managed System Hardware Setup | 34 |
| 3.10.2 Using the IEI iMAN Web GUI | 34 |
| 3.11 DRIVER INSTALLATION | 36 |
| 4 SYSTEM MAINTENANCE | 37 |
| 4.1 SYSTEM MAINTENANCE INTRODUCTION | 38 |
| 4.2 MOTHERBOARD REPLACEMENT | 38 |
| 4.3 SO-DIMM REPLACEMENT | 39 |
| 5 BIOS | 41 |
| 5.1 INTRODUCTION | 42 |
| 5.1.1 Starting Setup | 42 |
| 5.1.2 Using Setup | 42 |
| 5.1.3 Getting Help | 43 |
| 5.1.4 Unable to Reboot after Configuration Changes | 43 |
| 5.1.5 BIOS Menu Bar | 43 |
| 5.2 MAIN | 44 |
| 5.3 ADVANCED | 46 |
| 5.3.1 ACPI Settings | 47 |
| 5.3.2 Super IO Configuration | 48 |
| 5.3.2.1 Serial Port n Configuration | 49 |
| 5.3.3 iWDD H/W Monitor | 54 |
| 5.3.3.1 Smart Fan Mode Configuration | 55 |
| 5.3.4 RTC Wake Settings | 57 |
| 5.3.5 Serial Port Console Redirection | 58 |
| 5.3.6 CPU Configuration | 60 |
| 5.3.7 IDE Configuration | 63 |
| 5.3.8 USB Configuration | 64 |
| 5.4 CHIPSET | 65 |
| 5.4.1 North Bridge | 66 |

| | |
|---|-----------|
| 5.4.2 South Bridge..... | 66 |
| 5.4.2.1 PCI Express Configuration | 68 |
| 5.5 SECURITY..... | 69 |
| 5.6 BOOT..... | 70 |
| 5.7 EXIT..... | 72 |
| 6 PROGRAMMING OLED FOR DRPC-120-BTI-E5-OLED | 74 |
| 6.1 OVERVIEW..... | 75 |
| 6.2 OLED IMAGE EDITOR..... | 75 |
| 6.2.1 OLED Image Editor Installation | 75 |
| 6.2.2 Launching the OLED Image Editor..... | 78 |
| 6.2.3 Function List..... | 78 |
| 6.2.4 OLED Control..... | 79 |
| 6.2.5 OLED Erase Page..... | 80 |
| 6.3 DRPC100 DEMO PROGRAM..... | 81 |
| 6.3.1 Dialog Menu | 82 |
| 6.3.2 LCD Menu..... | 83 |
| 6.3.3 DEMO Menu..... | 84 |
| 7 INTERFACE CONNECTORS | 85 |
| 7.1 PERIPHERAL INTERFACE CONNECTORS..... | 86 |
| 7.2 INTERNAL PERIPHERAL CONNECTORS | 87 |
| 7.2.1 Audio Line-out Connector (<i>LINE_OUT1</i>) | 88 |
| 7.2.2 Audio Mic-in Connector (<i>MIC_IN1</i>)..... | 88 |
| 7.2.3 Battery Connector (<i>BAT1</i>)..... | 88 |
| 7.2.4 Chassis Intrusion Connector (<i>CHASSIE1</i>)..... | 88 |
| 7.2.5 CPU Fan Connector (<i>CPU_FAN1</i>)..... | 89 |
| 7.2.6 OLED/LED Signal Connector (<i>OLED1</i>)..... | 89 |
| 7.2.7 PCIe Mini Card Slot – Full Size (<i>M_PCIE1</i>) | 89 |
| 7.2.8 PCIe Mini Card Slot – Half Size (<i>MINI-PCIE1</i>) | 90 |
| 7.2.9 SATA 3Gb/s Connector (<i>SATA1</i>)..... | 91 |
| 7.2.10 SATA Power Connector (<i>SATA_PWR1</i>)..... | 92 |
| 7.2.11 SPI Flash Connector (<i>JSPI1</i>)..... | 92 |
| 7.2.12 SPI Flash Connector - EC (<i>JSPI2</i>)..... | 92 |
| 7.2.13 USB Connector (<i>USB1</i>)..... | 93 |

DRPC-120-BTi Embedded System

| | |
|---|------------|
| 7.3 EXTERNAL INTERFACE PANEL CONNECTORS | 93 |
| 7.3.1 Digital I/O Terminal Block (J1) | 94 |
| 7.3.2 Power Input Terminal Block (DC_IN1) | 94 |
| 7.3.3 RJ-45 LAN Connector (LAN1) | 94 |
| 7.3.4 RJ-45 LAN Connector (LAN2) | 95 |
| 7.3.5 RS-232 Serial Ports (COM1/2) | 95 |
| 7.3.6 RS-422/485 Serial Ports (COM3/4) | 95 |
| 7.3.7 USB 2.0 Connectors (USB2) | 96 |
| 7.3.8 USB 3.0 Connectors (USB1) | 96 |
| 7.3.9 VGA Connector (VGA1) | 96 |
| A REGULATORY COMPLIANCE | 98 |
| B SAFETY PRECAUTIONS | 103 |
| B.1 SAFETY PRECAUTIONS | 104 |
| B.1.1 General Safety Precautions | 104 |
| B.1.2 Anti-static Precautions | 105 |
| B.1.3 Explanation of Graphical Symbols | 105 |
| B.1.4 Product Disposal | 106 |
| B.2 MAINTENANCE AND CLEANING PRECAUTIONS | 106 |
| B.2.1 Maintenance and Cleaning | 106 |
| B.2.2 Cleaning Tools | 107 |
| C DIGITAL I/O INTERFACE | 108 |
| C.1 INTRODUCTION | 109 |
| C.2 ASSEMBLY LANGUAGE SAMPLE 1 | 110 |
| C.3 ASSEMBLY LANGUAGE SAMPLE 2 | 110 |
| D HAZARDOUS MATERIALS DISCLOSURE | 111 |
| D.1 HAZARDOUS MATERIALS DISCLOSURE TABLE FOR IPB PRODUCTS CERTIFIED AS ROHS COMPLIANT UNDER 2002/95/EC WITHOUT MERCURY | 112 |

List of Figures

| | |
|--|----|
| Figure 1-1: DRPC-120-BTi Series | 2 |
| Figure 1-2: DRPC-120-BTi-E5-LED Front Panel | 4 |
| Figure 1-3: DRPC-120-BTi-E5-OLED Front Panel | 5 |
| Figure 1-4: DRPC-120-BTi Top Panel..... | 6 |
| Figure 1-5: LED Indicators of DRPC-120-BTi-E5-LED..... | 6 |
| Figure 1-6: Physical Dimensions (millimeters)..... | 10 |
| Figure 3-1: Internal Access Panel Removal..... | 18 |
| Figure 3-2: HDD Installation | 19 |
| Figure 3-3: PCIe Mini Slot Location | 20 |
| Figure 3-4: Inserting the PCIe Mini Card into the Socket | 21 |
| Figure 3-5: Securing the PCIe Mini Card | 21 |
| Figure 3-6: IPMI Module Slot Location | 22 |
| Figure 3-7: IPMI Module Installation | 23 |
| Figure 3-8: Clear CMOS Button Location..... | 24 |
| Figure 3-9: AT/ATX Switch Location..... | 24 |
| Figure 3-10: DIN Rail Mounting Bracket Installation..... | 25 |
| Figure 3-11: Attach the Mounting Bracket to the DIN Rail | 25 |
| Figure 3-12: Mounting the System..... | 26 |
| Figure 3-13: DIO Terminal Block Pinout Location..... | 27 |
| Figure 3-14: RJ-45 Ethernet Connector..... | 28 |
| Figure 3-15: 3-pin Power Terminal Block Pinout Location..... | 29 |
| Figure 3-16: RS-232 Serial Port Pinout Location..... | 30 |
| Figure 3-17: RS-422/485 Serial Port Pinout Locations..... | 31 |
| Figure 3-18: VGA Connector | 33 |
| Figure 3-19: IEI iMAN Web Address..... | 34 |
| Figure 3-20: IEI iMAN Web GUI..... | 35 |
| Figure 4-1: SO-DIMM Module Location..... | 39 |
| Figure 4-2: SO-DIMM Module Installation..... | 40 |
| Figure 6-1: OLED Image Editor Setup Wizard | 76 |
| Figure 6-2: Select Installation Folder..... | 76 |

DRPC-120-BTi Embedded System

| | |
|---|-----------|
| Figure 6-3: Confirm Installation | 77 |
| Figure 6-4: Installation Complete..... | 77 |
| Figure 6-5: OLED Image Editor | 78 |
| Figure 6-6: Function List..... | 78 |
| Figure 6-7: OLED Control | 79 |
| Figure 6-8: OLED Erase Page..... | 80 |
| Figure 6-9: DR100 Demo Program Main Menu | 81 |
| Figure 6-10: Dialog Menu..... | 82 |
| Figure 6-11: LCD Menu | 83 |
| Figure 6-12: DEMO Menu | 84 |
| Figure 7-1: Main Board Layout Diagram (Front Side)..... | 86 |
| Figure 7-2: Main Board Layout Diagram (Solder Side)..... | 86 |

List of Tables

| | |
|---|----|
| Table 1-1: DRPC-120-BTi Model Variations | 2 |
| Table 1-2: DRPC-120-BTi-E5-LED LED Definitions | 7 |
| Table 1-3: Technical Specifications..... | 9 |
| Table 3-1: DIO Terminal Block Pinouts | 27 |
| Table 3-2: LAN1 Pinouts | 28 |
| Table 3-3: LAN2 Pinouts | 28 |
| Table 3-4: RJ-45 Ethernet Connector LEDs | 28 |
| Table 3-5: 3-pin Power Terminal Block Pinouts | 29 |
| Table 3-6: RS-232 Serial Port Pinouts | 30 |
| Table 3-7: RS-422/485 Serial Port Pinouts | 31 |
| Table 3-8: USB 2.0 Port (USB3/USB4) Pinouts | 32 |
| Table 3-9: USB 3.0 Port (USB1/USB2) Pinouts | 32 |
| Table 3-10: VGA Connector Pinouts..... | 33 |
| Table 5-1: BIOS Navigation Keys | 43 |
| Table 7-1: Peripheral Interface Connectors | 87 |
| Table 7-2: Audio Line-out Connector (LINE_OUT1) Pinouts..... | 88 |
| Table 7-3: Audio Mic-in Connector (MIC_IN1) Pinouts | 88 |
| Table 7-4: Battery Connector (BAT1) Pinouts | 88 |
| Table 7-5: Chassis Intrusion Connector (CHASSIE1) Pinouts..... | 88 |
| Table 7-6: CPU Fan Connector (CPU_FAN1) Pinouts..... | 89 |
| Table 7-7: OLED/LED Signal Connector (OLED1) Pinouts..... | 89 |
| Table 7-8: PCIe Mini Card Slot – Full Size (M_PCIE1) Pinouts..... | 90 |
| Table 7-9: PCIe Mini Card Slot – Half Size (MINI-PCIE1) Pinouts | 91 |
| Table 7-10: SATA 3Gb/s Connector (SATA1) Pinouts | 91 |
| Table 7-11: SATA Power Connector (SATA_PWR1) Pinouts | 92 |
| Table 7-12: SPI Flash Connector (JSPI1) Pinouts | 92 |
| Table 7-13: SPI Flash Connector - EC (JSPI2) Pinouts..... | 92 |
| Table 7-14: USB Connector (USB1) Pinouts..... | 93 |
| Table 7-15: Rear Panel Connectors | 93 |
| Table 7-16: Digital I/O Terminal Block (J1) Pinouts | 94 |

DRPC-120-BTi Embedded System

| | |
|--|----|
| Table 7-17: Power Input Terminal Block (DC_IN1) Pinouts..... | 94 |
| Table 7-18: RJ-45 LAN Connector (LAN1) Pinouts | 94 |
| Table 7-19: RJ-45 LAN Connector (LAN2) Pinouts | 95 |
| Table 7-20: RS-232 Serial Port (COM1/2) Pinouts | 95 |
| Table 7-21: RS-422/485 Serial Port (COM3/4) Pinouts | 95 |
| Table 7-22: USB 2.0 Connectors (USB2) Pinouts..... | 96 |
| Table 7-23: USB 3.0 Connectors (USB1) Pinouts..... | 96 |
| Table 7-24: VGA Connector (VGA1) Pinouts | 97 |

Chapter

1

Introduction

1.1 Overview



Figure 1-1: DRPC-120-BTi Series

The DRPC-120-BTi fanless embedded system is powered by the Intel® Atom™ E3845 processor. It is designed for harsh environment applications, and supports DIN rail mounting method.

The DRPC-120-BTi accepts a wide range of DC power input (9 V ~ 28 V), allowing it to be powered anywhere. Two USB 3.0, two USB 2.0, two GbE, two RS-232, two RS-422/485, and one 8-bit DIO provide rich I/O options for various applications.

1.2 Model Variations

The model variations of the DRPC-120-BTi are listed below.

| Model No. | Indicators |
|-------------------------|------------|
| DRPC-120-BTi-E5-LED/2G | LED |
| DRPC-120-BTi-E5-OLED/2G | OLED |

Table 1-1: DRPC-120-BTi Model Variations

DRPC-120-BTi Embedded System

1.3 Features

The DRPC-120-BTi features are listed below:

- 1.91 GHz quad-core Intel® Atom™ E3845 processor
- Low power consumption
- Fanless design
- DIN rail mounting support
- Preinstalled one 2 GB DDR3L SO-DIMM (system max. 8 GB)
- Supports one mSATA and one 2.5" SATA HDD
- Wide range DC power input (9 V ~ 28 V)
- Extended temperature fanless design supports -20°C ~ 60°C (with SSD)
- Two PCIe Mini card slots
- Serial interfaces with isolation protection
- 8-bit digital IO (4-bit output, 4-bit input)
- Supports two GbE, two USB 3.0, two USB 2.0, two RS-232 and two RS-422/485
- LED indicators (DRPC-120-BTi-E5-LED only)
- Programmable OLED display (DRPC-120-BTi-E5-OLED only)
- RoHS compliant

1.4 Connector Panel

1.4.1 Front Panel

The DRPC-120-BTi front panel contains:

- 2 x RJ-45 Gigabit LAN ports
- 2 x RS-232 serial ports with isolation
- 2 x RS-422/485 serial ports with isolation
- 2 x USB 3.0 ports
- 2 x USB 2.0 ports
- LED or OLED indicators
- Function keys (DRPC-120-BTi-E5-OLED only)

The overview of the front panels of both model are shown in **Figure 1-2** and **Figure 1-3**.




Figure 1-2: DRPC-120-BTi-E5-LED Front Panel

DRPC-120-BTi Embedded System




Figure 1-3: DRPC-120-BTi-E5-OLED Front Panel

1.4.2 Top Panel

The DRPC-120-BTi top panel contains:

- 1 x 8-bit digital I/O (Phoenix terminal block, 4-bit input/4-bit output)
- 1 x 9 V ~ 28 V DC power terminal block
- 1 x AT/ATX power switch
- 1 x HDMI connector
- 1 x Power button
- 1 x Reset button
- 1 x VGA connector

An overview of the top panel is shown in **Figure 1-4** below.




Figure 1-4: DRPC-120-BTi Top Panel

1.5 LED Indicators (DRPC-120-BTi-E5-LED Only)

The LED indicators on the front panel of the DRPC-120-BTi-E5-LED are shown in Figure 1-5.




Figure 1-5: LED Indicators of DRPC-120-BTi-E5-LED

All the LED definitions are listed in Table 1-2.

| LED | Color | Status | Description |
|-------|-------|----------|--------------------------|
| POWER | Red | On | System power is on |
| | | Off | System power is off |
| HDD | Green | Blinking | Storage device accessing |

DRPC-120-BTi Embedded System

| | | | |
|--|--------|-----|-----------------------------------|
| | | Off | Storage device not accessing |
| COM TX 1~4 | Yellow | On | COM port is transmitting data |
| | | Off | COM port is not transmitting data |
| COM RX 1~4 | Green | On | COM port is receiving data |
| | | Off | COM port is not receiving data |
| DIO DI 1~4* | Yellow | On | Active |
| | | Off | Inactive |
| DIO DO 1~4* | Green | On | Active |
| | | Off | Inactive |
| * When the DIO is set to pull-high, the DIO LED indicators always light up. When the DIO is set to pull-low, the DIO LED indicators are always off. | | | |

Table 1-2: DRPC-120-BTi-E5-LED LED Definitions

1.6 Programmable OLED Display (DRPC-120-BTi-E5-OLED Only)

For programming the OLED display on the front panel of the DRPC-120-BTi-E5-OLED, refer to **Chapter 6**.

1.7 Technical Specifications

The DRPC-120-BTi technical specifications are listed in **Table 1-3**.

| Specifications | |
|----------------------------|--|
| System | |
| CPU (SoC) | 1.91 GHz quad-core Intel® Atom™ E3845 processor |
| Memory | One 2 GB 204-pin DDR3L SO-DIMM preinstalled (system max. 8 GB) |
| Ethernet Controller | One Intel® I210 GbE controller One Intel® I211 GbE controller |
| Wireless | 802.11b/g/n 1T1R (optional) |
| IPMI | iRIS-2400 IPMI module (optional) |
| Supported OS | Microsoft Windows 8, Microsoft Windows Embedded Standard 7 |

| Specifications | |
|------------------------------|--|
| Storage | |
| HDD | One 2.5" SATA 3Gb/s HDD/SSD bay |
| mSATA | One PCIe Mini full-size card slot for mSATA module (SATA 3Gb/s) |
| I/O and Indicators | |
| Ethernet | 2 x RJ-45 ports |
| RS-232 | 2 x DB-9 serial ports with 3KV isolation protection |
| RS-422/RS-485 | 2 x DB-9 serial ports with 3KV isolation protection |
| USB | 2 x USB 3.0 ports 2 x USB 2.0 ports |
| Display | Supports resolution up to 1920 x 1200 1 x VGA port 1 x HDMI port |
| Digital I/O | 1 x Phoenix terminal block (8-bit, 4-bit input/4-bit output) |
| Interior Expansion | 1 x PCIe Mini full-size card slot (co-lay mSATA) 1 x PCIe Mini half-size card slot (reserved for optional Wi-Fi module) |
| Indicators | LED (for DRPC-120-BTi-E5-LED) OLED (for DRPC-120-BTi-E5-OLED) |
| Buttons | Power button Reset button |
| Power | |
| Power Input | 9 V ~ 28 V DC (3-pin terminal block) |
| Power Consumption | 12V@2.1A (1.91 GHz quad-core Intel® Atom™ E3845 processor with 2 GB memory) |
| AT/ATX Mode | AT/ATX switch |
| Environmental and Mechanical | |
| Mounting | DIN rail, desktop |

DRPC-120-BTi Embedded System

| Specifications | |
|------------------------------|---|
| Operating Temperature | -20°C~60°C with air flow (with SSD) |
| Storage Temperature | -30°C~70°C |
| Humidity | 5%~95%, non-condensing |
| Chassis Construction | Extruded aluminum alloy for fanless support |
| Color | Blue C + Black C |
| Operating Shock | Half-sine shock test 5G/11ms, 3 shocks per axis |
| Operating Vibration | MIL-STD-810F 514.5 C-2 (SSD) |
| Safety | CE/FCC |
| Weight (Net/Gross) | 1.4 kg/2.5 kg |
| Physical Dimensions | 74.8 mm x 140 mm x 171.5 mm (W x D x H) |

Table 1-3: Technical Specifications

1.8 Dimensions

The physical dimensions are shown below:




Figure 1-6: Physical Dimensions (millimeters)

Chapter

2

Unpacking

2.1 Anti-static Precautions



WARNING:

Failure to take ESD precautions during installation may result in permanent damage to the DRPC-120-BTi and severe injury to the user.

Electrostatic discharge (ESD) can cause serious damage to electronic components, including the DRPC-120-BTi. Dry climates are especially susceptible to ESD. It is therefore critical that whenever the DRPC-120-BTi or any other electrical component is handled, the following anti-static precautions are strictly adhered to.

- **Wear an anti-static wristband:** Wearing a simple anti-static wristband can help to prevent ESD from damaging the board.
- **Self-grounding:** Before handling the board, touch any grounded conducting material. During the time the board is handled, frequently touch any conducting materials that are connected to the ground.
- **Use an anti-static pad:** When configuring the DRPC-120-BTi, place it on an anti-static pad. This reduces the possibility of ESD damaging the DRPC-120-BTi.

2.2 Unpacking Precautions

When the DRPC-120-BTi is unpacked, please do the following:

- Follow the anti-static precautions outlined in **Section 2.1**.
- Make sure the packing box is facing upwards so the DRPC-120-BTi does not fall out of the box.
- Make sure all the components shown in **Section 2.3** are present.

DRPC-120-BTi Embedded System

2.3 Unpacking Checklist



NOTE:

If some of the components listed in the checklist below are missing, please do not proceed with the installation. Contact the IEI reseller or vendor you purchased the DRPC-120-BTi from or contact an IEI sales representative directly. To contact an IEI sales representative, please send an email to sales@ieiworld.com

The DRPC-120-BTi is shipped with the following components:

| Quantity | Item and Part Number | Image |
|-----------------|---|--|
| Standard | | |
| 1 | DRPC-120-BTi |  OR |
| 1 | 3-pin terminal block |  |
| 2 | 5-pin terminal block |  |
| 1 | SATA cable (P/N: 32801-000702-100-RS) |  |
| 1 | SATA power cable (P/N: 32102-010700-100-RS) |  |
| 1 | DIN rail mounting bracket (50 mm x 45 mm x 8.7 mm) |  |

| Quantity | Item and Part Number | Image |
|-----------------|--|--|
| Standard | | |
| 3 | Mounting bracket screw |  |
| 4 | Screw (for securing an PCIe Mini card) |  |
| 1 | One Key Recovery CD |  |
| 1 | User manual and driver CD |  |

The following table lists the optional items that can be purchased separately.

| Optional | |
|--|--|
| Power adapter (P/N: 63000-FSP036RAB610-RS) |  |
| Power cord, European standard, 1830 mm (P/N: 32000-000002-RS) |  |
| Power cord, American standard, 1830 mm (P/N: 32000-000025-RS) |  |
| Power cable, DC jack (5.5x2.5) to 3-pin terminal block, 200 mm (P/N: 32102-026500-100-RS) |  |

DRPC-120-BTi Embedded System

| Optional | |
|--|--|
| Flash disk, mSATA, 2GB~32GB, 0°C ~ 70°C (P/N: IPE-5200IM-xxx) | |
| Flash disk, mSATA, 2GB~32GB, -40°C ~ 85°C (P/N: IPE-5200VM-xxx) | |

Chapter

3

Installation

DRPC-120-BTi Embedded System

3.1 Installation Precautions

During installation, be aware of the precautions below:

- **Read the user manual:** The user manual provides a complete description of the DRPC-120-BTi, installation instructions and configuration options.
- **DANGER! Disconnect Power:** Power to the DRPC-120-BTi must be disconnected during the installation process. Failing to disconnect the power may cause severe injury to the body and/or damage to the system.
- **Qualified Personnel:** The DRPC-120-BTi must be installed and operated only by trained and qualified personnel. Maintenance, upgrades, or repairs may only be carried out by qualified personnel who are familiar with the associated dangers.
- **Air Circulation:** Make sure there is sufficient air circulation when installing the DRPC-120-BTi. The DRPC-120-BTi's cooling vents must not be obstructed by any objects. Blocking the vents can cause overheating of the DRPC-120-BTi. Leave at least 5 cm of clearance around the DRPC-120-BTi to prevent overheating.
- **Grounding:** The DRPC-120-BTi should be properly grounded. The voltage feeds must not be overloaded. Adjust the cabling and provide external overcharge protection per the electrical values indicated on the label attached to the back of the DRPC-120-BTi.

3.1.1 High Surface Temperature



WARNING:

Some surfaces of the equipment may become hot during operation.

The surface temperature may be up to several tens of degrees hotter than the ambient temperature. Under these circumstances, the equipment needs to be protected against accidental contact.

The equipment is intended for installation in a RESTRICTED ACCESS LOCATION.

- Access can only be gained by SERVICE PERSONS or by USERS who have been instructed about the reasons for the restrictions applied to the location and about any precautions that shall be taken.
- Access is through the use of a TOOL or lock and key, or other means of security, and is controlled by the authority responsible for the location.

3.2 Internal Access Panel Removal

Before installing or maintaining the internal components, the internal access panel must be removed from the DRPC-120-BTi. Follow the steps below to complete the task.

Step 1: Remove the three retention screws indicated in **Figure 3-1**.

Step 2: Slide the panel and gently lift the panel (**Figure 3-1**).



Figure 3-1: Internal Access Panel Removal

DRPC-120-BTi Embedded System

3.3 HDD Installation



WARNING:

Please install a solid state drive (SSD) when the DRPC-120-BTi is used in a harsh environment with extreme shock and vibration.

The DRPC-120-BTi allows installation of one 2.5" HDD/SSD. To install a HDD into the system, please follow the steps below.

- Step 1:** Remove the internal access panel from the DRPC-120-BTi. Please follow the instruction described in **Section 3.2**.
- Step 2:** Install the HDD into the bracket on the internal access panel, and secure the HDD with four retention screws (**Figure 3-2**).
- Step 3:** Connect the SATA cable and the SATA power cable to the rear of the HDD (**Figure 3-2**).
- Step 4:** Connect the SATA cable and the SATA power cable from the HDD to the SATA connector and SATA power connector on the motherboard (**Figure 3-2**).



Figure 3-2: HDD Installation

- Step 5:** Replace and secure the internal access panel to the system.

3.4 mSATA SSD Installation

The DRPC-120-BTi has one full-size PCIe Mini slot on the motherboard for mSATA SSD installation. To install the mSATA SSD, follow the instructions below.

Step 1: Remove the internal access panel from the DRPC-120-BTi. Please follow the instruction described in **Section 3.2**.

Step 2: Locate the PCIe Mini slot on the motherboard (**Figure 3-3**).




Figure 3-3: PCIe Mini Slot Location

Step 3: **Insert into the socket at an angle.** Line up the notch on the card with the notch on the connector. Slide the PCIe Mini card into the socket at an angle of about 20° (**Figure 3-4**).

DRPC-120-BTi Embedded System




Figure 3-4: Inserting the PCIe Mini Card into the Socket

Step 4: **Secure the PCIe Mini card.** Secure the PCIe Mini card with the supplied retention screws (**Figure 3-5**).




Figure 3-5: Securing the PCIe Mini Card

Step 5: Replace and secure the internal access panel to the system.

3.5 IPMI Module Installation (Optional)


**NOTE:**

The IPMI module slot is designed to install the IEI iRIS-2400 IPMI 2.0 module only. DO NOT install other modules into the IPMI module slot. Doing so may cause damage to the DRPC-120-BTi.

Please follow the steps below to install the iRIS-2400 module, and refer to **Section 3.10** for the setup procedure.

Step 1: Remove the internal access panel from the DRPC-120-BTi. Please follow the instruction described in **Section 3.2**.

Step 2: Locate the IPMI module slot on the motherboard (**Figure 3-3**).



IPMI Module Slot

Figure 3-6: IPMI Module Slot Location

Step 3: Align the iRIS-2400 module with the IPMI module slot. Align the notch on the module with the notch on the IPMI module slot.

Step 4: Insert the iRIS-2400 module. Push the module in at a 20° angle (**Figure 3-7**).

DRPC-120-BTi Embedded System

Step 5: Seat the iRIS-2400 module. Gently push downwards and the arms clip into place (**Figure 3-7**).




Figure 3-7: IPMI Module Installation

Step 6: Replace and secure the internal access panel to the system.

3.6 Clear CMOS

If the DRPC-120-BTi fails to boot due to improper BIOS settings, the clear CMOS button clears the CMOS data and resets the system BIOS information. To do this, push the clear CMOS button for a few seconds.

If the “CMOS Settings Wrong” message is displayed during the boot up process, the fault may be corrected by pressing the F1 to enter the CMOS Setup menu. Do one of the following:

- Enter the correct CMOS setting
- Load Optimal Defaults
- Load Failsafe Defaults.

After having done one of the above, save the changes and exit the CMOS Setup menu.

The clear CMOS button location is shown in **Figure 3-8** below.




Figure 3-8: Clear CMOS Button Location

3.7 AT/ATX Mode Selection

AT and ATX power modes can both be used on the DRPC-120-BTi. The selection is made through an AT/ATX switch on the top panel as shown below (**Figure 3-9**).




Figure 3-9: AT/ATX Switch Location

3.8 Mounting the System

The DRPC-120-BTi embedded system can be mounted onto a DIN rail. Follow the steps below to complete the task.

- Step 1:** Attach the supplied DIN rail mounting bracket to the rear panel of the embedded system. Secure the bracket to the embedded system with three retention screws (**Figure 3-10**).

DRPC-120-BTi Embedded System




Figure 3-10: DIN Rail Mounting Bracket Installation



NOTE:

In the diagrams below, the DIN rail is already installed on a surface or on a chassis.

Step 2: Attach the upper edge of the mounting bracket to the DIN rail as shown in

Figure 3-11.




Figure 3-11: Attach the Mounting Bracket to the DIN Rail

Step 3: Push the system toward the DIN rail until the mounting bracket clips into place firmly (**Figure 3-12**).




Figure 3-12: Mounting the System

3.9 External Peripheral Interface Connectors

The DRPC-120-BTi has the following connectors. Detailed descriptions of the connectors can be found in the subsections below.

- 8-bit DIO
- Ethernet
- Power input
- RS-232
- RS-422/485
- USB
- VGA
- HDMI

DRPC-120-BTi Embedded System

3.9.1 Digital Input/Output Terminal Block

- CN Label:** DIO
- CN Type:** Terminal block
- CN Location:** See **Figure 1-4**
- CN Pinouts:** See **Table 3-1** and **Figure 3-13**

The digital I/O terminal block provides programmable input and output for external devices. The digital I/O provides 4-bit output and 4-bit input. The pinouts for the digital I/O terminal block are listed in the table below.

| Pin | Description | Pin | Description |
|-----|--------------|-----|--------------|
| 1 | DGI_0 | 2 | DGO_0 |
| 3 | DGI_1 | 4 | DGO_1 |
| 5 | DGI_2 | 6 | DGO_2 |
| 7 | DGI_3 | 8 | DGO_3 |
| 9 | Isolator GND | 10 | Isolator Vin |

Table 3-1: DIO Terminal Block Pinouts




Figure 3-13: DIO Terminal Block Pinout Location

3.9.2 LAN Connectors

- CN Type:** RJ-45
- CN Location:** See **Figure 1-2**
- CN Pinouts:** See **Table 3-2** and **Table 3-3**

The LAN connectors allow connection to an external network.

| Pin | Description | Pin | Description |
|-----|-------------|-----|-------------|
| 20 | LAN1_MDI0P | 24 | LAN1_MDI2P |
| 21 | LAN1_MDI0N | 25 | LAN1_MDI2N |
| 22 | LAN1_MDI1P | 26 | LAN1_MDI3P |
| 23 | LAN1_MDI1N | 27 | LAN1_MDI3N |

Table 3-2: LAN1 Pinouts

| Pin | Description | Pin | Description |
|-----|-------------|-----|-------------|
| P2 | TRD2P0 | P6 | TRD2P2 |
| P3 | TRD2N0 | P7 | TRD2N2 |
| P4 | TRD2P1 | P8 | TRD2P3 |
| P5 | TRD2N1 | P9 | TRD2N3 |

Table 3-3: LAN2 Pinouts



Figure 3-14: RJ-45 Ethernet Connector

The RJ-45 Ethernet connector has two status LEDs, one green and one yellow. The green LED indicates activity on the port and the yellow LED indicates the port is linked. See **Table 3-4**.

| Activity/Link LED | | Speed LED | |
|-------------------|----------------|-----------|---------------------|
| STATUS | DESCRIPTION | STATUS | DESCRIPTION |
| Off | No link | Off | 10 Mbps connection |
| Yellow | Linked | Green | 100 Mbps connection |
| Blinking | TX/RX activity | Orange | 1 Gbps connection |

Table 3-4: RJ-45 Ethernet Connector LEDs

DRPC-120-BTi Embedded System

3.9.3 Power Input, 3-pin Terminal Block

- CN Type:** 3-pin terminal block
- CN Location:** See **Figure 1-4**
- CN Pinouts:** See **Table 3-5** and **Figure 3-15**

Connect the leads of a 9 V ~ 28 V DC power supply into the terminal block. Make sure that the power and ground wires are attached to the correct sockets of the connector.

| Pin | Description | Pin | Description |
|-----|--------------|-----|-------------|
| 1 | 9V~28V input | 3 | GND |
| 2 | 9V~28V input | | |

Table 3-5: 3-pin Power Terminal Block Pinouts




Figure 3-15: 3-pin Power Terminal Block Pinout Location

3.9.4 RS-232 Serial Port Connectors (COM1, COM2)

- CN Label:** COM1 and COM2
- CN Type:** DB-9 connectors
- CN Location:** See **Figure 1-2**
- CN Pinouts:** See **Table 3-6** and **Figure 3-16**

RS-232 serial port devices can be attached to the DB-9 ports on the front panel.

| Pin | Description | Pin | Description |
|-----|-------------|-----|-------------|
| 1 | DCD | 6 | DSR |
| 2 | RXD | 7 | RTS |
| 3 | TXD | 8 | CTS |
| 4 | DTR | 9 | RI |
| 5 | GND | | |

Table 3-6: RS-232 Serial Port Pinouts




Figure 3-16: RS-232 Serial Port Pinout Location

DRPC-120-BTi Embedded System

3.9.5 RS-422/485 Serial Port Connectors (COM3, COM4)

- CN Label:** COM3 and COM4
- CN Type:** DB-9 connectors
- CN Location:** See Figure 1-2
- CN Pinouts:** See Table 3-7 and Figure 3-17

RS-422/485 serial port devices can be attached to the DB-9 ports on the front panel.

| Pin | RS-422 | RS-485 |
|-----|-----------|----------|
| 1 | RS-422TX- | RS-485D- |
| 2 | RS-422TX+ | RS-485D+ |
| 3 | RS-422RX+ | -- |
| 4 | RS-422RX- | -- |
| 5 | GND | -- |
| 6 | -- | -- |
| 7 | -- | -- |
| 8 | -- | -- |
| 9 | -- | -- |

Table 3-7: RS-422/485 Serial Port Pinouts




Figure 3-17: RS-422/485 Serial Port Pinout Locations

3.9.6 USB Connectors

CN Type: USB port

CN Location: See **Figure 1-2**

CN Pinouts: See **Table 3-8** and **Table 3-9**

The USB ports are for connecting USB peripheral devices to the system. The USB 2.0 and USB 3.0 connector pinouts are listed below.

| Pin | Description | Pin | Description |
|-----|-------------|-----|-------------|
| 1 | VCC | 5 | VCC |
| 2 | DATA- | 6 | DATA- |
| 3 | DATA+ | 7 | DATA+ |
| 4 | GROUND | 8 | GROUND |

Table 3-8: USB 2.0 Port (USB3/USB4) Pinouts

| Pin | Description | Pin | Description |
|-----|-------------|-----|-------------|
| 1 | VCC | 10 | VCC |
| 2 | USB_DATA- | 11 | USB_DATA- |
| 3 | USB_DATA+ | 12 | USB_DATA+ |
| 4 | GND | 13 | GND |
| 5 | USB3_RX- | 14 | USB3_RX- |
| 6 | USB3_RX+ | 15 | USB3_RX+ |
| 7 | GND | 16 | GND |
| 8 | USB3_TX- | 17 | USB3_TX- |
| 9 | USB3_TX+ | 18 | USB3_TX+ |

Table 3-9: USB 3.0 Port (USB1/USB2) Pinouts

DRPC-120-BTi Embedded System

3.9.7 VGA Connector

- CN Label:** VGA
- CN Type:** 15-pin Female
- CN Location:** See **Figure 1-4**
- CN Pinouts:** See **Table 3-10**

The VGA connector connects to a monitor that accepts VGA video input.

| Pin | Description | Pin | Description |
|-----|-------------|-----|-------------|
| 1 | RED | 2 | GREEN |
| 3 | BLUE | 4 | NC |
| 5 | GND | 6 | GND |
| 7 | GND | 8 | GND |
| 9 | VCC | 10 | GND |
| 11 | NC | 12 | DDC DAT |
| 13 | HSYNC | 14 | VSYNC |
| 15 | DDCCLK | | |

Table 3-10: VGA Connector Pinouts




Figure 3-18: VGA Connector

3.10 IPMI Setup Procedure

The DRPC-120-BTi features Intelligent Platform Management Interface (IPMI) that helps lower the overall costs of server management by enabling users to maximize IT resource, save time and manage multiple systems. The DRPC-120-BTi supports IPMI 2.0 through the optional iRIS-2400 module. Follow the steps below to setup IPMI.

3.10.1 Managed System Hardware Setup

The hardware configuration of the managed system (DRPC-120-BTi) is described below.

Step 1: Install an iRIS-2400 module to the IPMI module socket (refer to **Section 3.5**).

Step 2: Make sure at least one DDR3 SO-DIMM is installed in one of the SO-DIMM sockets. If multiple SO-DIMMs are installed, all of the SO-DIMMs must be same size, same speed and same brand to get the best performance.

Step 3: Connect an Ethernet cable to **LAN2** RJ-45 connector (**Figure 1-2**).

3.10.2 Using the IEI iMAN Web GUI

To manage a client system from a remote console using IEI iMAN Web GUI, follow the steps below.

Step 1: Obtain the IP address of the managed system. It is recommended to use the IPMI Tool on the managed system to obtain the IP address. To use IPMI Tool to obtain IP address, follow the steps below:

- a. Copy the **ipmitool.exe** file to a bootable USB flash drive.
- b. Insert the USB flash drive to the DRPC-120-BTi.
- c. The DRPC-120-BTi boots from the USB flash drive.
- d. Enter the following command: **ipmitool 20 30 02 01 03 00 00**
(there is a space between each two-digit number).
- e. A serial of number shows. The last four two-digit hexadecimal numbers are the IP address. Convert the hexadecimal numbers to decimal numbers.

Step 2: On the remote management console, open a web browser. Enter the managed system IP address in the web browser (**Figure 3-19**).



Figure 3-19: IEI iMAN Web Address

Step 3: The login page appears in the web browser.

DRPC-120-BTi Embedded System

Step 4: Enter the user name and password to login the system. The default login username and password are:

-Username: **admin**

-Password: **admin**

Step 5: Press the login button to login the system.

Step 6: The IEI iMAN Web Interface appears.




Figure 3-20: IEI iMAN Web GUI



NOTE:

To understand how to use the IEI iMAN Web GUI, please refer to the iRIS-2400 Web GUI user manual in the utility CD came with the DRPC-120-BTi. The user manual describes each function in detail.

3.11 Driver Installation

**NOTE:**

The content of the CD may vary throughout the life cycle of the product and is subject to change without prior notice. Visit the IEI website or contact technical support for the latest updates.

All the drivers for the DRPC-120-BTi are on the utility CD that came with the system. The utility CD contains drivers for Windows 7 and Windows 8 operating systems. Please select the corresponding drivers for the system.

The following drivers can be installed on the **Windows 7** operating system:

- Chipset
- I/O driver
- Graphics (Intel® EMGD)
- TXE
- USB 3.0
- LAN
- Audio

The following drivers can be installed on the **Windows 8** operating system:

- Chipset
- Serial I/O driver (64-bit only)
- TXE
- Graphics
- LAN
- Audio

The DRPC-120-BTi-E5-OLED also comes with two programmable OLED display utilities that allow users to program their own APIs to show information on the OLED screen in graphic and text formats. Please refer to **Chapter 6** for detailed instruction.

Chapter

4

System Maintenance

4.1 System Maintenance Introduction

The following system components may require maintenance.

- Motherboard
- SO-DIMM module

If these components fail, they must be replaced. Please contact the system reseller or vendor to purchase replacement parts. Replacement instructions for the above listed components are described below.



WARNING!

Before accessing any DRPC-120-BTi internal components, make sure all power to the system has been disconnected. Failing to do so may cause severe damage to the DRPC-120-BTi and injury to the user.



WARNING!

Please take antistatic precautions when working with the internal components. The interior of the DRPC-120-BTi contains very sensitive electronic components. These components are easily damaged by electrostatic discharge (ESD). Before working with the internal components, make sure all anti-static precautions described earlier have been observed.

4.2 Motherboard Replacement

A user cannot replace a motherboard. If the motherboard fails it must be shipped back to IEI to be replaced. If the system motherboard has failed, please contact the system vendor, reseller or an IEI sales person directly.

DRPC-120-BTi Embedded System

4.3 SO-DIMM Replacement

To install/replace the SO-DIMM modules, please follow the steps below.

Step 1: Remove the internal access panel from the DRPC-120-BTi. Please follow the instruction described in **Section 3.2**.

Step 2: Locate the SO-DIMM module on the motherboard.




Figure 4-1: SO-DIMM Module Location

Step 3: Release the SO-DIMM module by pulling both the spring retainer clips outward from the socket.

Step 4: Grasp the SO-DIMM module by the edges and carefully pull it out of the socket.

Step 5: Install the new SO-DIMM module by pushing it into the socket at an angle (**Figure 4-2**).

Step 6: Gently push the rear of the SO-DIMM module down (**Figure 4-2**). The spring retainer clips clip into place and secure the SO-DIMM module in the socket.




Figure 4-2: SO-DIMM Module Installation

Step 7: Push the new SO-DIMM module until it engages and the white plastic end clips click into place. Make sure the end clips are fully secured after installation.

Chapter

5

BIOS

5.1 Introduction

The BIOS is programmed onto the BIOS chip. The BIOS setup program allows changes to certain system settings. This chapter outlines the options that can be changed.



NOTE:

Some of the BIOS options may vary throughout the life cycle of the product and are subject to change without prior notice.

5.1.1 Starting Setup

The UEFI BIOS is activated when the computer is turned on. The setup program can be activated in one of two ways.

1. Press the **DEL** or **F2** key as soon as the system is turned on or
2. Press the **DEL** or **F2** key when the “**Press DEL or F2 to enter SETUP**” message appears on the screen.

If the message disappears before the **DEL** or **F2** key is pressed, restart the computer and try again.

5.1.2 Using Setup

Use the arrow keys to highlight items, press **ENTER** to select, use the PageUp and PageDown keys to change entries, press **F1** for help and press **ESC** to quit. Navigation keys are shown in **Table 5-1**.

| Key | Function |
|-------------|--|
| Up arrow | Move to previous item |
| Down arrow | Move to next item |
| Left arrow | Move to the item on the left hand side |
| Right arrow | Move to the item on the right hand side |
| + | Increase the numeric value or make changes |

DRPC-120-BTi Embedded System

| Key | Function |
|---------|--|
| - | Decrease the numeric value or make changes |
| Esc key | Main Menu – Quit and not save changes into CMOS Status Page Setup Menu and Option Page Setup Menu -- Exit current page and return to Main Menu |
| F1 key | General help, only for Status Page Setup Menu and Option Page Setup Menu |
| F2 key | Load previous values |
| F3 key | Load optimized defaults |
| F4 key | Save changes and exit BIOS |

Table 5-1: BIOS Navigation Keys

5.1.3 Getting Help

When **F1** is pressed a small help window describing the appropriate keys to use and the possible selections for the highlighted item appears. To exit the Help Window press **Esc** or the **F1** key again.

5.1.4 Unable to Reboot after Configuration Changes

If the computer cannot boot after changes to the system configuration is made, CMOS defaults. Use the clear CMOS button described in **Chapter 3**.

5.1.5 BIOS Menu Bar

The **menu bar** on top of the BIOS screen has the following main items:

- Main – Changes the basic system configuration.
- Advanced – Changes the advanced system settings.
- Chipset – Changes the chipset settings.
- Security – Sets User and Supervisor Passwords.
- Boot – Changes the system boot configuration.
- Save & Exit – Selects exit options and loads default settings

The following sections completely describe the configuration options found in the menu items at the top of the BIOS screen and listed above.

5.2 Main

The **Main** BIOS menu (**BIOS Menu 1**) appears when the **BIOS Setup** program is entered.

The **Main** menu gives an overview of the basic system information.

| Aptio Setup Utility - Copyright (C) 2013 American Megatrends, Inc. | | | | | |
|--|----------|---------------------|----------|------|---|
| Main | Advanced | Chipset | Security | Boot | Save & Exit |
| BIOS Information | | | | | Set the Date. Use Tab to switch between Data elements. ----- ←→: Select Screen ↑ ↓: Select Item Enter>Select + -: Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save & Exit ESC: Exit |
| BIOS Vendor | | American Megatrends | | | |
| Core Version | | 5.009 | | | |
| Compliance | | UEFI 2.3;PI1.2 | | | |
| Project Version | | E445AT13.ROM | | | |
| Build Date and Time | | 09/18/2014 10:57:55 | | | |
| iWDD Vendor | | iEi | | | |
| iWDD Version | | E445ET18.bin | | | |
| IPMI Module | | N/A | | | |
| CPU Configuration | | | | | |
| Microcode Patch | | 901 | | | |
| BayTrail SoC | | D0 Stepping | | | |
| Memory Information | | | | | |
| Total Memory | | 2048 MB (LPDDR3) | | | |
| GOP Information | | | | | |
| Intel(R) GOP Driver | | [N/A] | | | |
| TXE Information | | | | | |
| Sec RC Version | | 00.05.00.00 | | | |
| TXE FW Version | | 01.00.02.1060 | | | |
| System Date | | [Tue 01/02/2010] | | | |
| System Time | | [15:10:27] | | | |
| Version 2.16.1242. Copyright (C) 2013 American Megatrends, Inc. | | | | | |

BIOS Menu 1: Main

→ BIOS Information

The **BIOS Information** lists a brief summary of the BIOS. The fields in **BIOS Information** cannot be changed. The items shown in the system overview include:

- **BIOS Vendor:** Installed BIOS vendor

DRPC-120-BTi Embedded System

- **Core Version:** Current BIOS version
- **Compliance:** Current compliant version
- **Project Version:** the board version
- **Build Date and Time:** Date and time the current BIOS version was made
- **iWDD Vendor:** Installed embedded controller vendor
- **iWDD Version:** Current embedded controller version

→ IPMI Module

The **IPMI Module** lists the installed IPMI module information.

→ CPU Information

The **CPU Information** lists a brief summary of the CPU. The fields in **CPU Information** cannot be changed. The items shown in the system overview include:

- **Microcode Patch:** Installed microcode patch
- **BayTrail SoC:** CPU stepping level

→ Memory Information

The **Memory Information** lists a brief summary of the system memory. The fields in **Memory Information** cannot be changed. The items shown in the system overview include:

- **Total Memory:** Current total memory of the system

→ GOP Information

The **GOP Information** lists a brief summary of the Graphics Output Protocol (GOP). The fields in **GOP Information** cannot be changed. The items shown in the system overview include:

- **Intel GOP Driver:** Installed Intel GOP driver

→ **TXE Information**

The **TXE Information** lists a brief summary of Intel® Trusted Execution Engine (TXE). The fields in **TXE Information** cannot be changed. The items shown in the system overview include:

- **Sec RC Version:** Current sec reference code version
- **TXE FW Version:** Current Intel® TXE firmware version

The System Overview field has two user configurable fields:

→ **System Date [xx/xx/xx]**

Use the **System Date** option to set the system date. Manually enter the day, month and year.

→ **System Time [xx:xx:xx]**

Use the **System Time** option to set the system time. Manually enter the hours, minutes and seconds.

5.3 Advanced

Use the **Advanced** menu (**BIOS Menu 2**) to configure the CPU and peripheral devices through the following sub-menus:



WARNING!

Setting the wrong values in the sections below may cause the system to malfunction. Make sure that the settings made are compatible with the hardware.

DRPC-120-BTi Embedded System

```

Aptio Setup Utility - Copyright (C) 2013 American Megatrends, Inc.
Main  Advanced  Chipset  Security  Boot  Save & Exit
-----
> ACPI Settings
> Super IO Configuration
> iWDD H/W Monitor
> RTC Wake Settings
> Serial Port Console Redirection
> CPU Configuration
> IDE Configuration
> USB Configuration
> ICP Board

System ACPI Parameters
-----
<=>: Select Screen
↑↓: Select Item
Enter>Select
+ - Change Opt.
F1  General Help
F2  Previous Values
F3  Optimized Defaults
F4  Save & Exit
ESC Exit

Version 2.16.1242. Copyright (C) 2013 American Megatrends, Inc.

```

BIOS Menu 2: Advanced

5.3.1 ACPI Settings

The **ACPI Settings** menu (**BIOS Menu 3**) configures the Advanced Configuration and Power Interface (ACPI) options.

```

Aptio Setup Utility - Copyright (C) 2013 American Megatrends, Inc.
Advanced
-----
ACPI Settings
ACPI Sleep State          [S3 (Suspend to RAM)]

Select the highest ACPI
sleep state the system
will enter when the
SUSPEND button is
pressed.
-----
<=>: Select Screen
↑↓: Select Item
Enter>Select
+ - Change Opt.
F1  General Help
F2  Previous Values
F3  Optimized Defaults
F4  Save & Exit
ESC Exit

Version 2.16.1242. Copyright (C) 2013 American Megatrends, Inc.

```

BIOS Menu 3: ACPI Configuration

→ ACPI Sleep State [S3 (Suspend to RAM)]

Use the **ACPI Sleep State** option to specify the sleep state the system enters when it is not being used.

- **S3 (Suspend to DEFAULT RAM)** The caches are flushed and the CPU is powered off. Power to the RAM is maintained. The computer returns slower to a working state, but more power is saved.

5.3.2 Super IO Configuration

Use the **Super IO Configuration** menu (**BIOS Menu 4**) to set or change the configurations for the serial ports.

```


Aptio Setup Utility - Copyright (C) 2013 American Megatrends, Inc.
  Advanced
F81866 Super IO Configuration
F81866 Super IO Chip          F81866
> Serial Port 1 Configuration
> Serial Port 2 Configuration
> Serial Port 3 Configuration
> Serial Port 4 Configuration
Set Parameters of Serial
Port 1 (COMA)
-----
←→: Select Screen
↑ ↓: Select Item
EnterSelect
+ - Change Opt.
F1  General Help
F2  Previous Values
F3  Optimized Defaults
F4  Save & Exit
ESC Exit
Version 2.16.1242. Copyright (C) 2013 American Megatrends, Inc.
  
```

BIOS Menu 4: Super IO Configuration

DRPC-120-BTi Embedded System

5.3.2.1 Serial Port n Configuration

Use the **Serial Port n Configuration** menu (**BIOS Menu 5**) to configure the serial port n.



BIOS Menu 5: Serial Port n Configuration Menu

5.3.2.1.1 Serial Port 1 Configuration

→ Serial Port [Enabled]

Use the **Serial Port** option to enable or disable the serial port.

- **Disabled** Disable the serial port
- **Enabled** **DEFAULT** Enable the serial port

→ Change Settings [Auto]

Use the **Change Settings** option to change the serial port IO port address and interrupt address.

- **Auto** **DEFAULT** The serial port IO port address and interrupt address are automatically detected.
- **IO=3F8h;**
IRQ=4 Serial Port I/O port address is 3F8h and the interrupt address is IRQ4

- **IO=3F8h;**
IRQ=3, 4,
5, 6, 7, 9,
10, 11, 12

Serial Port I/O port address is 3F8h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12
- **IO=2F8h;**
IRQ=3, 4,
5, 6, 7, 9,
10, 11, 12

Serial Port I/O port address is 2F8h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12
- **IO=3E8h;**
IRQ=3, 4,
5, 6, 7, 9,
10, 11, 12

Serial Port I/O port address is 3E8h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12
- **IO=2E8h;**
IRQ=3, 4,
5, 6, 7, 9,
10, 11, 12

Serial Port I/O port address is 2E8h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12

5.3.2.1.2 Serial Port 2 Configuration

→ Serial Port [Enabled]

Use the **Serial Port** option to enable or disable the serial port.

- **Disabled** Disable the serial port
- **Enabled** **DEFAULT** Enable the serial port

→ Change Settings [Auto]

Use the **Change Settings** option to change the serial port IO port address and interrupt address.

- **Auto** **DEFAULT** The serial port IO port address and interrupt address are automatically detected.

DRPC-120-BTi Embedded System

- **IO=2F8h;**
IRQ=3 Serial Port I/O port address is 2F8h and the interrupt address is IRQ3
- **IO=3F8h;**
IRQ=3, 4,
5, 6, 7, 9,
10, 11, 12 Serial Port I/O port address is 3F8h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12
- **IO=2F8h;**
IRQ=3, 4,
5, 6, 7, 9,
10, 11, 12 Serial Port I/O port address is 2F8h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12
- **IO=3E8h;**
IRQ=3, 4,
5, 6, 7, 9,
10, 11, 12 Serial Port I/O port address is 3E8h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12
- **IO=2E8h;**
IRQ=3, 4,
5, 6, 7, 9,
10, 11, 12 Serial Port I/O port address is 2E8h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12

5.3.2.1.3 Serial Port 3 Configuration

→ Serial Port [Enabled]

Use the **Serial Port** option to enable or disable the serial port.

- **Disabled** Disable the serial port
- **Enabled** **DEFAULT** Enable the serial port

→ Change Settings [Auto]

Use the **Change Settings** option to change the serial port IO port address and interrupt address.

| | | | |
|---|--|----------------|---|
| → | Auto | DEFAULT | The serial port IO port address and interrupt address are automatically detected. |
| → | IO=3E8h; IRQ=7 | | Serial Port I/O port address is 3E8h and the interrupt address is IRQ7 |
| → | IO=3F8h; IRQ=3, 4, 5, 6, 7, 9, 10, 11, 12 | | Serial Port I/O port address is 3F8h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12 |
| → | IO=2F8h; IRQ=3, 4, 5, 6, 7, 9, 10, 11, 12 | | Serial Port I/O port address is 2F8h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12 |
| → | IO=3E8h; IRQ=3, 4, 5, 6, 7, 9, 10, 11, 12 | | Serial Port I/O port address is 3E8h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12 |
| → | IO=2E8h; IRQ=3, 4, 5, 6, 7, 9, 10, 11, 12 | | Serial Port I/O port address is 2E8h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12 |
| → | IO=2F0h; IRQ=3, 4, 5, 6, 7, 9, 10, 11, 12 | | Serial Port I/O port address is 2F0h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12 |
| → | IO=2E0h; IRQ=3, 4, 5, 6, 7, 9, 10, 11, 12 | | Serial Port I/O port address is 2E0h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12 |

DRPC-120-BTi Embedded System

5.3.2.1.4 Serial Port 4 Configuration

→ Serial Port [Enabled]

Use the **Serial Port** option to enable or disable the serial port.

- **Disabled** Disable the serial port
- **Enabled DEFAULT** Enable the serial port

→ Change Settings [Auto]

Use the **Change Settings** option to change the serial port IO port address and interrupt address.

- **Auto DEFAULT** The serial port IO port address and interrupt address are automatically detected.
- **IO=2E8h;
IRQ=7** Serial Port I/O port address is 2E8h and the interrupt address is IRQ7
- **IO=3F8h;
IRQ=3, 4,
5, 6, 7, 9,
10, 11, 12** Serial Port I/O port address is 3F8h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12
- **IO=2F8h;
IRQ=3, 4,
5, 6, 7, 9,
10, 11, 12** Serial Port I/O port address is 2F8h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12
- **IO=3E8h;
IRQ=3, 4,
5, 6, 7, 9,
10, 11, 12** Serial Port I/O port address is 3E8h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12
- **IO=2E8h;
IRQ=3, 4,
5, 6, 7, 9,
10, 11, 12** Serial Port I/O port address is 2E8h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12

- ➔ **IO=2F0h;** Serial Port I/O port address is 2F0h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12
- ➔ **IO=2E0h;** Serial Port I/O port address is 2E0h and the interrupt address is IRQ3, 4, 5, 6, 7, 9, 10, 11, 12

5.3.3 iWDD H/W Monitor

The **iWDD H/W Monitor** menu (**BIOS Menu 6**) contains the fan configuration submenus and displays operating temperature and system voltages.

```

Aptio Setup Utility - Copyright (C) 2013 American Megatrends, Inc.
  Advanced
PC Health Status
CPU temperature           :+43 °C
System temperature       :+39 °C
CPU_FAN1 Speed           :N/A
CPU_CORE                 :+0.886 V
+5V                      :+4.968 V
+V12                     :+11.866 V
+DDR                     :+1.342 V
+5VSB                    :+4.953 V
+3.3V                    :+3.291 V
+3.3VSB                  :+3.271 V
> Smart Fan Mode Configuration
Smart Fan Mode Select
-----
<=>: Select Screen
↑ ↓: Select Item
EnterSelect
+ - Change Opt.
F1  General Help
F2  Previous Values
F3  Optimized Defaults
F4  Save & Exit
ESC Exit
Version 2.16.1242. Copyright (C) 2013 American Megatrends, Inc.
  
```

BIOS Menu 6: iWDD H/W Monitor

➔ PC Health Status

The following system parameters and values are shown. The system parameters that are monitored are:

DRPC-120-BTi Embedded System

- System Temperatures:
 - CPU Temperature
 - System Temperature
- Fan Speed:
 - CPU Fan
- Voltages:
 - CPU_CORE
 - +5V
 - +V12
 - +DDR
 - +5VSB
 - +3.3V
 - +3.3VSB

5.3.3.1 Smart Fan Mode Configuration

Use the **Smart Fan Mode Configuration** submenu (**BIOS Menu 7**) to configure smart fan temperature and speed settings.

```

Aptio Setup Utility - Copyright (C) 2013 American Megatrends, Inc.
  Advanced
Smart Fan Mode Configuration
CPU_FAN1 Smart Fan Control      [Auto Mode]
Auto mode fan start temperature 50
Auto mode fan off temperature  40
Auto mode fan start PWM        30
Auto mode fan slope PWM        1

Smart Fan Mode Select
-----
<->: Select Screen
↑ ↓: Select Item
Enter>Select
+ -  Change Opt.
F1   General Help
F2   Previous Values
F3   Optimized Defaults
F4   Save & Exit
ESC  Exit

Version 2.16.1242. Copyright (C) 2013 American Megatrends, Inc.
  
```

BIOS Menu 7: Smart Fan Mode Configuration

➔ CPU Smart Fan Control [Auto PWM Mode]

Use the **CPU Smart Fan Control** option to configure the CPU smart fan.

- **Manual Mode** The fan spins at the speed set in Manual Mode settings.
- **Auto Mode** **DEFAULT** The fan adjusts its speed using Auto Mode settings.

→ **Auto mode fan start temperature**

Use the + or – key to change the **Auto mode fan start temperature** value. Enter a decimal number between 1 and 100.

→ **Auto mode fan off temperature**

Use the + or – key to change the **Auto mode fan off temperature** value. Enter a decimal number between 1 and 100.

→ **Auto mode fan start PWM**

Use the + or – key to change the **Auto mode fan start PWM** value. Enter a decimal number between 1 and 100.


→ **Auto mode fan slope PWM**

Use the + or – key to change the **Auto mode fan slope PWM** value. Enter a decimal number between 1 and 64.

DRPC-120-BTi Embedded System

5.3.4 RTC Wake Settings

The **RTC Wake Settings** menu (**BIOS Menu 8**) configures RTC wake event.



BIOS Menu 8: RTC Wake Settings

→ Wake System with Fixed Time [Disabled]

Use the **Wake System with Fixed Time** option to specify the time the system should be roused from a suspended state.

- **Disabled** **DEFAULT** The real time clock (RTC) cannot generate a wake event

DRPC-120-BTi Embedded System

→ Console Redirection [Disabled]

Use **Console Redirection** option to enable or disable the console redirection function.

- **Disabled** **DEFAULT** Disabled the console redirection function
- **Enabled** Enabled the console redirection function

The following options are available in the **Console Redirection Settings** submenu when the Console Redirection option is enabled.

→ Terminal Type [ANSI]

Use the **Terminal Type** option to specify the remote terminal type.

- **VT100** The target terminal type is VT100
- **VT100+** The target terminal type is VT100+
- **VT-UTF8** The target terminal type is VT-UTF8
- **ANSI** **DEFAULT** The target terminal type is ANSI

→ Bits per second [115200]

Use the **Bits per second** option to specify the serial port transmission speed. The speed must match the other side. Long or noisy lines may require lower speeds.

- **9600** Sets the serial port transmission speed at 9600.
- **19200** Sets the serial port transmission speed at 19200.
- **38400** Sets the serial port transmission speed at 38400.
- **57600** Sets the serial port transmission speed at 57600.
- **115200** **DEFAULT** Sets the serial port transmission speed at 115200.

→ Data Bits [8]

Use the **Data Bits** option to specify the number of data bits.

- **7** Sets the data bits at 7.

→ 8 **DEFAULT** Sets the data bits at 8.

→ **Parity [None]**

Use the **Parity** option to specify the parity bit that can be sent with the data bits for detecting the transmission errors.

→ **None** **DEFAULT** No parity bit is sent with the data bits.

→ **Even** The parity bit is 0 if the number of ones in the data bits is even.

→ **Odd** The parity bit is 0 if the number of ones in the data bits is odd.

→ **Mark** The parity bit is always 1. This option does not provide error detection.

→ **Space** The parity bit is always 0. This option does not provide error detection.

→ **Stop Bits [1]**

Use the **Stop Bits** option to specify the number of stop bits used to indicate the end of a serial data packet. Communication with slow devices may require more than 1 stop bit.

→ 1 **DEFAULT** Sets the number of stop bits at 1.

→ 2 Sets the number of stop bits at 2.

5.3.6 CPU Configuration

Use the **CPU Configuration** BIOS menu (**BIOS Menu 10**) to view detailed CPU specifications and configure the CPU.

DRPC-120-BTi Embedded System

Aptio Setup Utility - Copyright (C) 2013 American Megatrends, Inc.

Advanced

| | | |
|---------------------------------|---------------|---|
| CPU Configuration | | Number enabled, a VMM can utilize the additional hardware capabilities provided by Vanderpool Technology. |
| Intel(R) Celeron(R) CPU E3845 @ | 1.91GHz | |
| CPU Signature | 30679 | |
| Microcode Patch | 901 | |
| Max CPU Speed | 1910 MHz | |
| Min CPU Speed | 500 MHz | |
| Processor Cores | 4 | |
| Intel HT Technology | Not Supported | |
| Intel VT-x Technology | Supported | |
| ----- | | |
| L1 Data Cache | 24 kB x 4 | ←→: Select Screen |
| L1 Code Cache | 32 kB x 4 | ↑ ↓: Select Item |
| L2 Cache | 1024 kB x 2 | EnterSelect |
| L3 Cache | Not Present | + - Change Opt. |
| 64-bit | Supported | F1 General Help |
| Intel Virtualization Technology | [Enabled] | F2 Previous Values |
| EIST | [Enabled] | F3 Optimized Defaults |
| | | F4 Save & Exit |
| | | ESC Exit |

Version 2.16.1242. Copyright (C) 2013 American Megatrends, Inc.

BIOS Menu 10: CPU Configuration

The CPU Configuration menu (**BIOS Menu 10**) lists the following CPU details:

- CPU Signature: Lists the CPU signature value.
- Microcode Patch: Lists the microcode patch being used.
- Max CPU Speed: Lists the maximum CPU processing speed.
- Min CPU Speed: Lists the minimum CPU processing speed.
- Processor Cores: Lists the number of the processor core
- Intel HT Technology: Indicates if Intel HT Technology is supported by the CPU.
- Intel VT-x Technology: Indicates if Intel VT-x Technology is supported by the CPU.
- L1 Data Cache: Lists the amount of data storage space on the L1 cache.
- L1 Code Cache: Lists the amount of code storage space on the L1 cache.
- L2 Cache: Lists the amount of storage space on the L2 cache.
- L3 Cache: Lists the amount of storage space on the L3 cache.

→ Intel Virtualization Technology [Enabled]

Use the **Intel Virtualization Technology** option to enable or disable virtualization on the system. When combined with third party software, Intel® Virtualization technology allows several OSs to run on the same system at the same time.

→ Disabled Disables Intel Virtualization Technology.

→ Enabled **DEFAULT** Enables Intel Virtualization Technology.

→ EIST [Enabled]

Use the **EIST** option to enable or disable Enhanced Intel SpeedStep® Technology (EIST).


→ Disabled Disables Enhanced Intel SpeedStep® Technology.

→ Enabled **DEFAULT** Enables Enhanced Intel SpeedStep® Technology.

DRPC-120-BTi Embedded System

5.3.7 IDE Configuration

Use the **IDE Configuration** menu (**BIOS Menu 11**) to change and/or set the configuration of the SATA devices installed in the system.



BIOS Menu 11: IDE Configuration

→ Serial-ATA (SATA) [Enabled]

Use the **Serial-ATA (SATA)** option to enable or disable the serial ATA port.

- **Enabled** **DEFAULT** Enables the SATA port.
- **Disabled** Disables the SATA port.


→ SATA Mode [IDE Mode]

Use the **SATA Mode** option to configure SATA devices as normal IDE devices.

- **IDE Mode** **DEFAULT** Configures SATA devices as normal IDE device.
- **AHCI Mode** Configures SATA devices as AHCI device.

5.3.8 USB Configuration

Use the **USB Configuration** menu (**BIOS Menu 12**) to read USB configuration information and configure the USB settings.



BIOS Menu 12: USB Configuration

➔ **USB Devices**

The **USB Devices Enabled** field lists the USB devices that are enabled on the system

➔ **Legacy USB Support [Enabled]**

Use the **Legacy USB Support** BIOS option to enable USB mouse and USB keyboard support. Normally if this option is not enabled, any attached USB mouse or USB keyboard does not become available until a USB compatible operating system is fully booted with all USB drivers loaded. When this option is enabled, any attached USB mouse or USB keyboard can control the system even when there is no USB driver loaded onto the system.

➔ **Enabled** **DEFAULT** Legacy USB support enabled

DRPC-120-BTi Embedded System

- ➔ **Disabled** Legacy USB support disabled
- ➔ **Auto** Legacy USB support disabled if no USB devices are connected

5.4 Chipset

Use the **Chipset** menu (**BIOS Menu 13**) to access the North Bridge and South Bridge subsystem configuration menus.



WARNING!

Setting the wrong values for the Chipset BIOS selections in the Chipset BIOS menu may cause the system to malfunction.

```

Aptio Setup Utility - Copyright (C) 2013 American Megatrends, Inc.
Main   Advanced  Chipset  Security  Boot   Save & Exit
-----
> North Bridge
> South Bridge

North Bridge Parameters.


-----
<->: Select Screen
↑ ↓: Select Item
Enter Select
+ - Change Opt.
F1  General Help
F2  Previous Values
F3  Optimized Defaults
F4  Save & Exit
ESC Exit

Version 2.16.1242. Copyright (C) 2013 American Megatrends, Inc.
    
```

BIOS Menu 13: Chipset

5.4.1 North Bridge


Use the **North Bridge** menu (**BIOS Menu 14**) to configure the north bridge parameters.



BIOS Menu 14: North Bridge

5.4.2 South Bridge

Use the **South Bridge** menu (**BIOS Menu 15**) to configure the south bridge parameters.



BIOS Menu 15: South Bridge

DRPC-120-BTi Embedded System

→ Restore on AC Power Loss [Last State]

Use the **Restore on AC Power Loss** BIOS option to specify what state the system returns to if there is a sudden loss of power to the system.

- **Power Off** The system remains turned off
- **Power On** The system turns on
- **Last State** **DEFAULT** The system returns to its previous state. If it was on, it turns itself on. If it was off, it remains off.

→ Audio Controller [Enabled]

Use the **Audio Controller** BIOS option to enable or disable the High Definition Audio controller.

- **Disabled** The High Definition Audio controller is disabled.
- **Enabled** **DEFAULT** The High Definition Audio controller is enabled.


→ XHCI Mode [Smart Auto]

Use the **XHCI Mode** BIOS option to configure the USB xHCI (USB 3.0) controller.

- **Enabled** Enable the xHCI controller. USB 3.0 ports behave as USB 3.0 ports.
- **Smart** **DEFAULT** Allow the use of USB 3.0 devices prior to OS boot. USB 3.0 ports function as USB 3.0 ports even during a reboot.
- **Auto**

5.4.2.1 PCI Express Configuration

Use the **PCI Express Configuration** submenu (**BIOS Menu 16**) to configure the PCI Express slots.



BIOS Menu 16: PCI Express Configuration

→ PCI Express Port 2 [Enabled]

Use the **PCI Express Port 2** option to enable or disable the corresponding PCIe slot.

- **Enabled** **DEFAULT** The PCIe slot is enabled.
- **Disabled** The PCIe slot is disabled.

→ Speed [Auto]


Use the **Speed** option to configure the speed of the corresponding PCIe slot.

- **Auto** **DEFAULT**
- Gen 2
- Gen 1

DRPC-120-BTi Embedded System

5.5 Security

Use the **Security** menu (**BIOS Menu 17**) to set system and user passwords.



BIOS Menu 17: Security

➔ Administrator Password


Use the **Administrator Password** to set or change an administrator password.

➔ User Password

Use the **User Password** to set or change a user password.

5.6 Boot

Use the **Boot** menu (**BIOS Menu 18**) to configure system boot options.



BIOS Menu 18: Boot

→ Bootup NumLock State [On]

Use the **Bootup NumLock State** BIOS option to specify if the number lock setting must be modified during boot up.

→ **On** **DEFAULT** Allows the Number Lock on the keyboard to be enabled automatically when the computer system boots up. This allows the immediate use of the 10-key numeric keypad located on the right side of the keyboard. To confirm this, the Number Lock LED light on the keyboard is lit.

→ **Off** Does not enable the keyboard Number Lock automatically. To use the 10-keys on the keyboard, press the Number Lock key located on the upper left-hand corner of the 10-key pad. The Number Lock LED on the keyboard lights up when the Number Lock is engaged.

DRPC-120-BTi Embedded System

→ Quiet Boot [Enabled]

Use the **Quiet Boot** BIOS option to select the screen display when the system boots.

- **Disabled** Normal POST messages displayed
- **Enabled** **DEFAULT** OEM Logo displayed instead of POST messages

→ UEFI Boot [Disabled]

Use the **UEFI Boot** option to enable or disable to boot from a UEFI device.

- **Enabled** Enable to boot from a UEFI device.
- **Disabled** **DEFAULT** Disable to boot from a UEFI device.

→ Launch PXE OpROM [Disabled]

Use the **Launch PXE OpROM** option to enable or disable boot option for legacy network devices.

- **Disabled** **DEFAULT** Ignore all PXE Option ROMs
- **Enabled** Load PXE Option ROMs

→ Option ROM Messages [Force BIOS]

Use the **Option ROM Messages** option to set the Option ROM display mode.

- **Force BIOS** **DEFAULT** Sets display mode to force BIOS.
- **Keep Current** Sets display mode to current.

5.7 Exit

Use the **Exit** menu (**BIOS Menu 19**) to load default BIOS values, optimal failsafe values and to save configuration changes.

```
Aptio Setup Utility - Copyright (C) 2013 American Megatrends, Inc.
Main   Advanced  Chipset  Security  Boot   Save & Exit
-----
Save Changes and Reset
Discard Changes and Reset

Restore Defaults
Save as User Defaults
Restore User Defaults

Reset the system after
saving the changes.

-----
<->: Select Screen
↑ ↓: Select Item
Enter>Select
+ -  Change Opt.
F1   General Help
F2   Previous Values
F3   Optimized Defaults
F4   Save & Exit
ESC  Exit

Version 2.16.1242. Copyright (C) 2013 American Megatrends, Inc.
```

BIOS Menu 19:Exit

→ Save Changes and Reset

Use the **Save Changes and Reset** option to save the changes made to the BIOS options and reset the system.

→ Discard Changes and Reset

Use the **Discard Changes and Reset** option to exit the system without saving the changes made to the BIOS configuration setup program.

→ Restore Defaults

Use the **Restore Defaults** option to load the optimal default values for each of the parameters on the Setup menus. **F3 key can be used for this operation.**

DRPC-120-BTi Embedded System

→ Save as User Defaults

Use the **Save as User Defaults** option to save the changes done so far as user defaults.

→ Restore User Defaults

Use the **Restore User Defaults** option to restore the user defaults to all the setup options.

Chapter

6

Programming OLED for DRPC-120-BTi-E5-OLED

DRPC-120-BTi Embedded System

6.1 Overview

The DRPC-120-BTi-E5-OLED comes with two programmable OLED display utilities that allow users to program their own APIs to show information on the OLED screen in graphic and text formats. The two utilities are listed below.

- **OLED Image Editor:** Allows displaying information in graphic format.
- **DR100 Demo Program:** Allows displaying information in text format.

The following sections describe how to use these two utilities in detail.

6.2 OLED Image Editor

The OLED Image Editor allows displaying information in graphic format.

6.2.1 OLED Image Editor Installation

To install the OLED Image Editor, please follow the steps below.

- Step 1:** Insert the driver CD into an optical disk drive connected to the system.
- Step 2:** Locate the **setup** file in the **OLEDImageEditor** folder of the driver CD. Double click the setup file to start the installation.
- Step 3:** The OLED Image Editor Setup Wizard welcome window appears (**Figure 6-1**). Click **Next** to start.




Figure 6-1: OLED Image Editor Setup Wizard

Step 4: Select a folder for OLED Image Editor Installation in **Figure 6-2**. Click **Next** to continue.




Figure 6-2: Select Installation Folder

DRPC-120-BTi Embedded System

Step 5: The following screen appears. Click **Next** to confirm the installation.




Figure 6-3: Confirm Installation

Step 6: The system starts installing the OLED Image Editor.

Step 7: When the OLED Image Editor is successfully installed, the following window appears. Click **Close** to exit.




Figure 6-4: Installation Complete

6.2.2 Launching the OLED Image Editor

To launch the OLED Image Editor, double click the OLED Image Editor icon on the desktop.




Figure 6-5: OLED Image Editor

6.2.3 Function List

The OLED Image Editor provides picture drawing function. Users can draw simple pictures on the Canvas.




Figure 6-6: Function List

DRPC-120-BTi Embedded System

- **OPEN:**
Allows loading a 24-bit BMP file. The resolution of the 24-bit BMP file must be 128 x 64.
- **SAVE:**
Allows saving as a BMP file. The file must be saved as 24-bit BMP with 128 x 64 resolution.
- **CLEAR:**
Clears the picture drew on the Canvas.
- **Pen Color:**
Sets the pen color to black or white.

6.2.4 OLED Control

The OLED Control allows users to setup the OLED module. Refer to the **DRPC100-OLED UART Protocol** reference manual packaged in the driver CD for detailed setup.




Figure 6-7: OLED Control

- **PAGE(0-511):**
Allows users to indicate a page number to burn or display the image of the page using the function buttons below it. The range of page number is 0 ~ 511.
- **Burn image:**
Clicks to burn the image on the Canvas into the OLED module according to

the indicated page number. When writing an image into the OLED module, the OLED Status field displays “The page is under writing. Please wait...”. Please be patient and wait for several seconds. When finished, “Write Page Done” is displayed.

- **Display:**
Clicks to show the corresponding image on the OLED display according to the indicated page number.
- **Clear Screen:**
Clicks to clear the OLED screen.

6.2.5 OLED Erase Page

The OLED Erase Page allows users to erase the images in the indicated page numbers. The range of page number is 0 ~ 511. Please note that the **Start PAGE** must be smaller than the **End Page**.




Figure 6-8: OLED Erase Page

When the page number range is set, click **Erase**. A warning message will appear to remind users the estimated time. Click **Yes** to continue. The OLED Status field will display the erasing status.

To erase all images, set the page number from 0 to 511.

DRPC-120-BTi Embedded System

6.3 DRPC100 Demo Program

**NOTE:**

Refer to the **DRPC100-Matrix LED UART Protocol** reference manual packaged in the driver CD for detailed setup.

The DRPC100 Demo Program allows displaying information in text format.

To launch the DRPC100, double click the **DRPC100_OLED_DEMO** file located in the **DEMO APP** folder of the driver CD. The main menu appears as below.




Figure 6-9: DR100 Demo Program Main Menu

6.3.1 Dialog Menu

The Dialog menu allows users to clear the OLED screen, and get ID.





Figure 6-10: Dialog Menu

- **Get ID:** Click to get ID.
- **Clr OLED:** Click to clear the OLED screen.
- **Close:** Click to return to the main menu.
- **Clear:** Clear the messages.

DRPC-120-BTi Embedded System

6.3.2 LCD Menu

The LCD menu allows users to edit the text for displaying on the OLED screen of the system.



The screenshot shows a graphical user interface for editing text. It features a vertical list of seven text input fields. The first three fields contain the text "CPU info", "HDD info", and "CF info" respectively. Below the input fields are three buttons: "Send" (with a dotted border), "Clear", and "Close".

Figure 6-11: LCD Menu

- **Send:** Click to send the input text to be displayed on the OLED display.
- **Clear:** Clear the input text.
- **Close:** Click to return to the main menu.

6.3.3 DEMO Menu

The DEMO menu lists the activities of the function keys. Click **Close** to return to the main menu.




Figure 6-12: DEMO Menu

Chapter

7

Interface Connectors

7.1 Peripheral Interface Connectors

The DRPC-120-BTi embedded system motherboard comes with a number of peripheral interface connectors and configuration jumpers. The connector locations are shown in **Table 7-1** and **Figure 7-2**. The Pin 1 locations of the on-board connectors are also indicated in the diagrams. The connector pinouts for these connectors are listed in the following sections.




Figure 7-1: Main Board Layout Diagram (Front Side)




Figure 7-2: Main Board Layout Diagram (Solder Side)

DRPC-120-BTi Embedded System

7.2 Internal Peripheral Connectors

Internal peripheral connectors are found on the motherboard and are only accessible when the motherboard is outside of the chassis. The table below shows a list of the peripheral interface connectors on the DRPC-120-BTi motherboard. Pinouts of these connectors can be found in the following sections.

| Connector | Type | Label |
|-----------------------------|--------------------------|------------|
| Audio line-out connector | 4-pin wafer | LINE_OUT1 |
| Audio mic-in connector | 4-pin wafer | MIC_IN1 |
| Battery connector | 2-pin wafer | BAT1 |
| Chassis intrusion connector | 2-pin header | CHASSIE1 |
| CPU fan connector | 3-pin wafer | CPU_FAN1 |
| IPMI module slot | SO-DIMM connector | IPMI1 |
| Memory slot | SO-DIMM connector | DIMM1 |
| OLED/LED signal connector | 8-pin connector | OLED1 |
| PCIe Mini slot (full-size) | Full-size PCIe Mini slot | M_PCIE1 |
| PCIe Mini slot (half-size) | Half-size PCIe Mini slot | MINI-PCIE1 |
| SATA connector | SATA connector | SATA1 |
| SATA power connector | 2-pin wafer | SATA_PWR1 |
| SPI flash connector | 6-pin wafer | JSPI1 |
| SPI flash connector (EC) | 6-pin wafer | JSPI2 |
| USB connector | 4-pin header | USB1 |

Table 7-1: Peripheral Interface Connectors

7.2.1 Audio Line-out Connector (LINE_OUT1)

| PIN NO. | DESCRIPTION |
|---------|-------------|
| 1 | SPK_R |
| 2 | AUDIO_GND |
| 3 | AUDIO_GND |
| 4 | SPK_L |

Table 7-2: Audio Line-out Connector (LINE_OUT1) Pinouts

7.2.2 Audio Mic-in Connector (MIC_IN1)

| PIN NO. | DESCRIPTION |
|---------|-------------|
| 1 | MIC_R |
| 2 | AUDIO_GND |
| 3 | AUDIO_GND |
| 4 | MIC_L |

Table 7-3: Audio Mic-in Connector (MIC_IN1) Pinouts

7.2.3 Battery Connector (BAT1)

| PIN NO. | DESCRIPTION |
|---------|-------------|
| 1 | VBATT |
| 2 | GND |

Table 7-4: Battery Connector (BAT1) Pinouts

7.2.4 Chassis Intrusion Connector (CHASSIE1)

| PIN NO. | DESCRIPTION |
|---------|-------------|
| 1 | Case Open |
| 2 | GND |

Table 7-5: Chassis Intrusion Connector (CHASSIE1) Pinouts

7.2.5 CPU Fan Connector (CPU_FAN1)

| PIN NO. | DESCRIPTION |
|---------|-------------|
| 1 | GND |
| 2 | +5V |
| 3 | FANIO |
| 4 | PWM |

Table 7-6: CPU Fan Connector (CPU_FAN1) Pinouts

7.2.6 OLED/LED Signal Connector (OLED1)

| PIN NO. | DESCRIPTION | PIN NO. | DESCRIPTION |
|---------|-------------|---------|-------------|
| 1 | +3V | 2 | +12V |
| 3 | LED_SDA | 4 | GPIO |
| 5 | LED_SCL | 6 | GPIO |
| 7 | GND | 8 | RESET# |

Table 7-7: OLED/LED Signal Connector (OLED1) Pinouts

7.2.7 PCIe Mini Card Slot – Full Size (M_PCIE1)

| PIN NO. | DESCRIPTION | PIN NO. | DESCRIPTION |
|---------|---------------|---------|-------------|
| 1 | PCIE_WAKE# | 2 | VCC3 |
| 3 | N/C | 4 | GND |
| 5 | N/C | 6 | 1.5V |
| 7 | N/C | 8 | N/C |
| 9 | GND | 10 | N/C |
| 11 | CLK- | 12 | N/C |
| 13 | CLK+ | 14 | N/C |
| 15 | GND | 16 | N/C |
| 17 | PCIRST# | 18 | GND |
| 19 | N/C | 20 | VCC3 |
| 21 | GND | 22 | PCIRST# |
| 23 | PERN/SATA_RXP | 24 | 3VDual |
| 25 | PERP/SATA_RXN | 26 | GND |

| PIN NO. | DESCRIPTION | PIN NO. | DESCRIPTION |
|---------|---------------|---------|-------------|
| 27 | GND | 28 | 1.5V |
| 29 | GND | 30 | SMBCLK |
| 31 | PETN/SATA_TXN | 32 | SMBDATA |
| 33 | PETP/SATA_TXP | 34 | GND |
| 35 | GND | 36 | USBD- |
| 37 | N/C | 38 | USBD+ |
| 39 | N/C | 40 | GND |
| 41 | N/C | 42 | N/C |
| 43 | N/C | 44 | N/C |
| 45 | N/C | 46 | N/C |
| 47 | N/C | 48 | 1.5V |
| 49 | N/C | 50 | GND |
| 51 | N/C | 52 | VCC3 |

Table 7-8: PCIe Mini Card Slot – Full Size (M_PCIE1) Pinouts

7.2.8 PCIe Mini Card Slot – Half Size (MINI-PCIE1)

| PIN NO. | DESCRIPTION | PIN NO. | DESCRIPTION |
|---------|-------------|---------|-------------|
| 1 | PCIE_WAKE# | 2 | VCC3 |
| 3 | N/C | 4 | GND |
| 5 | N/C | 6 | 1.5V |
| 7 | N/C | 8 | N/C |
| 9 | GND | 10 | N/C |
| 11 | CLK- | 12 | N/C |
| 13 | CLK+ | 14 | N/C |
| 15 | GND | 16 | N/C |
| 17 | PCIRST# | 18 | GND |
| 19 | N/C | 20 | VCC3 |
| 21 | GND | 22 | PCIRST# |
| 23 | PERN2 | 24 | 3VDual |
| 25 | PERP2 | 26 | GND |
| 27 | GND | 28 | 1.5V |

DRPC-120-BTi Embedded System

| PIN NO. | DESCRIPTION | PIN NO. | DESCRIPTION |
|---------|-------------|---------|-------------|
| 29 | GND | 30 | SMBCLK |
| 31 | PETN2 | 32 | SMBDATA |
| 33 | PETP2 | 34 | GND |
| 35 | GND | 36 | USBD- |
| 37 | N/C | 38 | USBD+ |
| 39 | N/C | 40 | GND |
| 41 | N/C | 42 | N/C |
| 43 | N/C | 44 | N/C |
| 45 | N/C | 46 | N/C |
| 47 | N/C | 48 | 1.5V |
| 49 | N/C | 50 | GND |
| 51 | N/C | 52 | VCC3 |

Table 7-9: PCIe Mini Card Slot – Half Size (MINI-PCIE1) Pinouts

7.2.9 SATA 3Gb/s Connector (SATA1)

| PIN NO. | DESCRIPTION |
|---------|-------------|
| 1 | GND |
| 2 | TX+ |
| 3 | TX- |
| 4 | GND |
| 5 | RX- |
| 6 | RX+ |
| 7 | GND |

Table 7-10: SATA 3Gb/s Connector (SATA1) Pinouts

7.2.10 SATA Power Connector (SATA_PWR1)

| PIN NO. | DESCRIPTION |
|---------|------------------|
| 1 | 5V (supports 1A) |
| 2 | GND |

Table 7-11: SATA Power Connector (SATA_PWR1) Pinouts

7.2.11 SPI Flash Connector (JSPI1)

| PIN NO. | DESCRIPTION |
|---------|-------------|
| 1 | SPI_VCC |
| 2 | SPI_CS |
| 3 | SPI_SO_SW |
| 4 | SPI_CLK_SW |
| 5 | SPI_SI_SW |
| 6 | GND |

Table 7-12: SPI Flash Connector (JSPI1) Pinouts

7.2.12 SPI Flash Connector - EC (JSPI2)

| PIN NO. | DESCRIPTION |
|---------|---------------|
| 1 | SPI_VCC_EC |
| 2 | SPI_CS#_EC |
| 3 | SPI_SO_SW_EC |
| 4 | SPI_CLK_SW_EC |
| 5 | SPI_SI_SW_EC |
| 6 | GND |

Table 7-13: SPI Flash Connector - EC (JSPI2) Pinouts

DRPC-120-BTi Embedded System

7.2.13 USB Connector (USB1)

| PIN NO. | DESCRIPTION |
|---------|-------------|
| 1 | VCC |
| 2 | USB_DATA- |
| 3 | USB_DAT+ |
| 4 | GND |

Table 7-14: USB Connector (USB1) Pinouts

7.3 External Interface Panel Connectors

The table below lists the rear panel connectors on the DRPC-120-BTi motherboard. Pinouts of these connectors can be found in the following sections.

| Connector | Type | Label |
|----------------------------------|----------------------|-----------|
| Digital I/O terminal block | 5-pin terminal block | J1 |
| HDMI connector | HDMI | HDMI1 |
| Power button | Push button | PWR_BTN1 |
| Power input terminal block | 3-pin terminal block | DC_IN1 |
| Reset button | Push button | RST_BTN1 |
| RJ-45 LAN and USB 2.0 connectors | RJ-45, USB 2.0 | LAN2_USB2 |
| RJ-45 LAN and USB 3.0 connectors | RJ-45, USB 3.0 | LAN1_USB1 |
| RS-232 serial ports | D-sub 9 male | COM1/2 |
| RS-422/485 serial ports | D-sub 9 male | COM3/4 |
| VGA connector | D-sub 15 female | VGA1 |

Table 7-15: Rear Panel Connectors

7.3.1 Digital I/O Terminal Block (J1)

| PIN NO. | DESCRIPTION | PIN NO. | DESCRIPTION |
|---------|--------------|---------|--------------|
| 1 | DGI_0 | 2 | DGO_0 |
| 3 | DGI_1 | 4 | DGO_1 |
| 5 | DGI_2 | 6 | DGO_2 |
| 7 | DGI_3 | 8 | DGO_3 |
| 9 | Isolator GND | 10 | Isolator Vin |

Table 7-16: Digital I/O Terminal Block (J1) Pinouts

7.3.2 Power Input Terminal Block (DC_IN1)

| PIN NO. | DESCRIPTION |
|---------|-------------|
| 1 | 9~28V input |
| 2 | 9~28V input |
| 3 | GND |

Table 7-17: Power Input Terminal Block (DC_IN1) Pinouts

7.3.3 RJ-45 LAN Connector (LAN1)

| PIN NO. | DESCRIPTION | PIN NO. | DESCRIPTION |
|---------|-------------|---------|-------------|
| 20 | LAN1_MDI0P | 24 | LAN1_MDI2P |
| 21 | LAN1_MDI0N | 25 | LAN1_MDI2N |
| 22 | LAN1_MDI1P | 26 | LAN1_MDI3P |
| 23 | LAN1_MDI1N | 27 | LAN1_MDI3N |

Table 7-18: RJ-45 LAN Connector (LAN1) Pinouts

DRPC-120-BTi Embedded System

7.3.4 RJ-45 LAN Connector (LAN2)

| PIN NO. | DESCRIPTION | PIN NO. | DESCRIPTION |
|---------|-------------|---------|-------------|
| P2 | TRD2P0 | P6 | TRD2P2 |
| P3 | TRD2N0 | P7 | TRD2N2 |
| P4 | TRD2P1 | P8 | TRD2P3 |
| P5 | TRD2N1 | P9 | TRD2N3 |

Table 7-19: RJ-45 LAN Connector (LAN2) Pinouts

7.3.5 RS-232 Serial Ports (COM1/2)

| PIN NO. | DESCRIPTION | PIN NO. | DESCRIPTION |
|---------|-------------|---------|-------------|
| 1 | DCD | 6 | DSR |
| 2 | RXD | 7 | RTS |
| 3 | TXD | 8 | CTS |
| 4 | DTR | 9 | RI |
| 5 | GND | | |

Table 7-20: RS-232 Serial Port (COM1/2) Pinouts

7.3.6 RS-422/485 Serial Ports (COM3/4)

| PIN NO. | DESCRIPTION | PIN NO. | DESCRIPTION |
|---------|------------------|---------|-------------|
| 1 | RS422TX-/RS485D- | 6 | NC |
| 2 | RS422TX+/RS485D+ | 7 | NC |
| 3 | RS422RX+ | 8 | NC |
| 4 | RS422RX- | 9 | NC |
| 5 | GND | | |

Table 7-21: RS-422/485 Serial Port (COM3/4) Pinouts

7.3.7 USB 2.0 Connectors (USB2)

| PIN NO. | DESCRIPTION | PIN NO. | DESCRIPTION |
|---------|-------------|---------|-------------|
| 1 | VCC | 10 | VCC |
| 2 | DATA- | 11 | DATA- |
| 3 | DATA+ | 12 | DATA+ |
| 4 | GROUND | 13 | GROUND |

Table 7-22: USB 2.0 Connectors (USB2) Pinouts

7.3.8 USB 3.0 Connectors (USB1)

| PIN NO. | DESCRIPTION | PIN NO. | DESCRIPTION |
|---------|-------------|---------|-------------|
| 1 | VCC | 10 | VCC |
| 2 | USB_DATA- | 11 | USB_DATA- |
| 3 | USB_DATA+ | 12 | USB_DATA+ |
| 4 | GND | 13 | GND |
| 5 | USB3_RX- | 14 | USB3_RX- |
| 6 | USB3_RX+ | 15 | USB3_RX+ |
| 7 | GND | 16 | GND |
| 8 | USB3_TX- | 17 | USB3_TX- |
| 9 | USB3_TX+ | 18 | USB3_TX+ |

Table 7-23: USB 3.0 Connectors (USB1) Pinouts

7.3.9 VGA Connector (VGA1)

| PIN NO. | DESCRIPTION | PIN NO. | DESCRIPTION |
|---------|-------------|---------|-------------|
| 1 | RED | 2 | GREEN |
| 3 | BLUE | 4 | NC |
| 5 | GND | 6 | GND |
| 7 | GND | 8 | GND |
| 9 | VCC | 10 | GND |
| 11 | NC | 12 | DDC DAT |

DRPC-120-BTi Embedded System

| | | | |
|----|--------|----|-------|
| 13 | HSYNC | 14 | VSYNC |
| 15 | DDCCLK | | |

Table 7-24: VGA Connector (VGA1) Pinouts

Appendix

A

Regulatory Compliance

DECLARATION OF CONFORMITY

This equipment is in conformity with the following EU directives:

- EMC Directive 2004/108/EC
- Low-Voltage Directive 2006/95/EC
- RoHS II Directive 2011/65/EU
- Ecodesign Directive 2009/125/EC

If the user modifies and/or install other devices in the equipment, the CE conformity declaration may no longer apply.

If this equipment has telecommunications functionality, it also complies with the requirements of the R&TTE Directive 1999/5/EC.

English

IEI Integration Corp declares that this equipment is in compliance with the essential requirements and other relevant provisions of Directive 1999/5/EC.

Български [Bulgarian]

IEI Integration Corp. декларира, че този оборудване е в съответствие със съществените изисквания и другите приложими правила на Директива 1999/5/EC.

Česky [Czech]

IEI Integration Corp tímto prohlašuje, že tento zařizení je ve shodě se základními požadavky a dalšími příslušnými ustanoveními směrnice 1999/5/ES.

Dansk [Danish]

IEI Integration Corp erklærer herved, at følgende udstyr overholder de væsentlige krav og øvrige relevante krav i direktiv 1999/5/EF.

Deutsch [German]

IEI Integration Corp, erklärt dieses Gerät entspricht den grundlegenden Anforderungen und den weiteren entsprechenden Vorgaben der Richtlinie 1999/5/EU.

Eesti [Estonian]

IEI Integration Corp deklareerib seadme seadme vastavust direktiivi 1999/5/EÜ põhinõuetele ja nimetatud direktiivist tulenevatele teistele asjakohastele sätetele.

Español [Spanish]

IEI Integration Corp declara que el equipo cumple con los requisitos esenciales y cualesquiera otras disposiciones aplicables o exigibles de la Directiva 1999/5/CE.

Ελληνική [Greek]

IEI Integration Corp ΔΗΛΩΝΕΙ ΟΤΙ ΕΞΟΠΛΙΣΜΟΣ ΣΥΜΜΟΡΦΩΝΕΤΑΙ ΠΡΟΣ ΤΙΣ ΟΥΣΙΩΔΕΙΣ ΑΠΑΙΤΗΣΕΙΣ ΚΑΙ ΤΙΣ ΛΟΙΠΕΣ ΣΧΕΤΙΚΕΣ ΔΙΑΤΑΞΕΙΣ ΤΗΣ ΟΔΗΓΙΑΣ 1999/5/EK.

Français [French]

IEI Integration Corp déclare que l'appareil est conforme aux exigences essentielles et aux autres dispositions pertinentes de la directive 1999/5/CE.

Italiano [Italian]

IEI Integration Corp dichiara che questo apparecchio è conforme ai requisiti essenziali ed alle altre disposizioni pertinenti stabilite dalla direttiva 1999/5/CE.

Latviski [Latvian]

IEI Integration Corp deklarē, ka iekārta atbilst būtiskajām prasībām un citiem ar to saistītajiem noteikumiem Direktīvas 1999/5/EK.

Lietuvių [Lithuanian]

IEI Integration Corp deklaruoja, kad šis įranga atitinka esminius reikalavimus ir kitas 1999/5/EB Direktyvos nuostatas.

Nederlands [Dutch]

IEI Integration Corp dat het toestel toestel in overeenstemming is met de essentiële eisen en de andere relevante bepalingen van richtlijn 1999/5/EG.

Malti [Maltese]

IEI Integration Corp jiddikjara li dan prodott jikkonforma mal-ħtiġijiet essenzjali u ma provvedimenti oħrajn relevanti li hemm fid-Dirrettiva 1999/5/EC.

Magyar [Hungarian]

IEI Integration Corp nyilatkozom, hogy a berendezés megfelel a vonatkozó alapvető követelményeknek és az 1999/5/EC irányelv egyéb előírásainak.

Polski [Polish]

IEI Integration Corp oświadcza, że wyrobu jest zgodny z zasadniczymi wymogami oraz pozostałymi stosownymi postanowieniami Dyrektywy 1999/5/EC.

Português [Portuguese]

IEI Integration Corp declara que este equipamento está conforme com os requisitos essenciais e outras disposições da Directiva 1999/5/CE.

DRPC-120-BTi Embedded System

Româna [Romanian]

IEI Integration Corp declară că acest echipament este în conformitate cu cerințele esențiale și cu celelalte prevederi relevante ale Directivei 1999/5/CE.

Slovensko [Slovenian]

IEI Integration Corp izjavlja, da je ta opreme v skladu z bistvenimi zahtevami in ostalimi relevantnimi določili direktive 1999/5/ES.

Slovensky [Slovak]

IEI Integration Corp týmto vyhlasuje, že zariadenia spĺňa základné požiadavky a všetky príslušné ustanovenia Smernice 1999/5/ES.

Suomi [Finnish]

IEI Integration Corp vakuuttaa täten että laitteet on direktiivin 1999/5/EY oleellisten vaatimusten ja sitä koskevien direktiivin muiden ehtojen mukainen.

Svenska [Swedish]

IEI Integration Corp förklarar att denna utrustningstyp står i överensstämmelse med de väsentliga egenskapskrav och övriga relevanta bestämmelser som framgår av direktiv 1999/5/EG.

FCC WARNING

This equipment complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- This device may not cause harmful interference, and
- This device must accept any interference received, including interference that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

Appendix

B

Safety Precautions

B.1 Safety Precautions



WARNING:

The precautions outlined in this appendix should be strictly followed. Failure to follow these precautions may result in permanent damage to the DRPC-120-BTi.

Please follow the safety precautions outlined in the sections that follow:

B.1.1 General Safety Precautions

Please ensure the following safety precautions are adhered to at all times.

- ***Make sure the power is turned off and the power cord is disconnected*** when moving, installing or modifying the system.
- ***Do not apply voltage levels that exceed the specified voltage range.*** Doing so may cause fire and/or an electrical shock.
- ***Electric shocks can occur*** if opened while still powered on.
- ***Do not drop or insert any objects*** into the ventilation openings.
- ***If considerable amounts of dust, water, or fluids enter the system***, turn off the power supply immediately, unplug the power cord, and contact the system vendor.
- **DO NOT:**
 - Drop the system against a hard surface.
 - Strike or exert excessive force onto the LCD panel.
 - Touch any of the LCD panels with a sharp object
 - In a site where the ambient temperature exceeds the rated temperature

DRPC-120-BTi Embedded System

B.1.2 Anti-static Precautions



WARNING:

Failure to take ESD precautions during the installation of the DRPC-120-BTi may result in permanent damage to the DRPC-120-BTi and severe injury to the user.

Electrostatic discharge (ESD) can cause serious damage to electronic components, including the DRPC-120-BTi. Dry climates are especially susceptible to ESD. It is therefore critical that whenever the DRPC-120-BTi is opened and any of the electrical components are handled, the following anti-static precautions are strictly adhered to.

- ***Wear an anti-static wristband:*** Wearing a simple anti-static wristband can help to prevent ESD from damaging any electrical component.
- ***Self-grounding:*** Before handling any electrical component, touch any grounded conducting material. During the time the electrical component is handled, frequently touch any conducting materials that are connected to the ground.
- ***Use an anti-static pad:*** When configuring or working with an electrical component, place it on an anti-static pad. This reduces the possibility of ESD damage.
- ***Only handle the edges of the electrical component:*** When handling the electrical component, hold the electrical component by its edges.

B.1.3 Explanation of Graphical Symbols



This symbol warns the user that the part has this symbol is hot. Therefore, it is dangerous to make any kind of contact with this part.



This symbol alerts the user that important information concerning the operation and maintenance of this unit has been included. Therefore, the information should be read carefully in order to avoid any problems.


B.1.4 Product Disposal

**CAUTION:**

Risk of explosion if battery is replaced by an incorrect type. Only certified engineers should replace the on-board battery.

Dispose of used batteries according to instructions and local regulations.

- Outside the European Union - If you wish to dispose of used electrical and electronic products outside the European Union, please contact your local authority so as to comply with the correct disposal method.
- Within the European Union:



EU-wide legislation, as implemented in each Member State, requires that waste electrical and electronic products carrying the mark (left) must be disposed of separately from normal household waste. This includes monitors and electrical accessories, such as signal cables or power cords.

When you need to dispose of your display products, please follow the guidance of your local authority, or ask the shop where you purchased the product. The mark on electrical and electronic products only applies to the current European Union Member States.

Please follow the national guidelines for electrical and electronic product disposal.

B.2 Maintenance and Cleaning Precautions

When maintaining or cleaning the DRPC-120-BTi, please follow the guidelines below.

B.2.1 Maintenance and Cleaning

Prior to cleaning any part or component of the DRPC-120-BTi, please read the details below.

DRPC-120-BTi Embedded System

- The interior of the DRPC-120-BTi does not require cleaning. Keep fluids away from the DRPC-120-BTi interior.
- Be cautious of all small removable components when vacuuming the DRPC-120-BTi.
- Turn the DRPC-120-BTi off before cleaning the DRPC-120-BTi.
- Never drop any objects or liquids through the openings of the DRPC-120-BTi.
- Be cautious of any possible allergic reactions to solvents or chemicals used when cleaning the DRPC-120-BTi.
- Avoid eating, drinking and smoking within vicinity of the DRPC-120-BTi.

B.2.2 Cleaning Tools

Some components in the DRPC-120-BTi may only be cleaned using a product specifically designed for the purpose. In such case, the product will be explicitly mentioned in the cleaning tips. Below is a list of items to use when cleaning the DRPC-120-BTi.

- **Cloth** – Although paper towels or tissues can be used, a soft, clean piece of cloth is recommended when cleaning the DRPC-120-BTi.
- **Water or rubbing alcohol** – A cloth moistened with water or rubbing alcohol can be used to clean the DRPC-120-BTi.
- **Using solvents** – The use of solvents is not recommended when cleaning the DRPC-120-BTi as they may damage the plastic parts.
- **Vacuum cleaner** – Using a vacuum specifically designed for computers is one of the best methods of cleaning the DRPC-120-BTi. Dust and dirt can restrict the airflow in the DRPC-120-BTi and cause its circuitry to corrode.
- **Cotton swabs** - Cotton swabs moistened with rubbing alcohol or water are excellent tools for wiping hard to reach areas.
- **Foam swabs** - Whenever possible, it is best to use lint free swabs such as foam swabs for cleaning.

Appendix

C

Digital I/O Interface

DRPC-120-BTi Embedded System

C.1 Introduction

The DIO connector on the DRPC-120-BTi is interfaced to GPIO ports on the Super I/O chipset. The DIO has both 4-bit digital inputs and 4-bit digital outputs. The digital inputs and digital outputs are generally control signals that control the on/off circuit of external devices or TTL devices. Data can be read or written to the selected address to enable the DIO functions.



NOTE:

For further information, please refer to the datasheet for the Super I/O chipset.

The BIOS interrupt call **INT 15H** controls the digital I/O.

INT 15H:

| | |
|----------------------|---------------------------------|
| AH – 6FH | |
| <u>Sub-function:</u> | |
| AL – 8 | : Set the digital port as INPUT |
| AL | : Digital I/O input value |

C.2 Assembly Language Sample 1

```
MOV    AX, 6F08H    ;setting the digital port as input
INT    15H          ;
```

AL low byte = value

| | |
|----------------------|---------------------------------|
| AH – 6FH | |
| <u>Sub-function:</u> | |
| AL – 9 | :Set the digital port as OUTPUT |
| BL | :Digital I/O input value |

C.3 Assembly Language Sample 2

```
MOV    AX, 6F09H    ;setting the digital port as output
MOV    BL, 09H      ;digital value is 09H
INT    15H          ;
```

Digital Output is 1001b

Appendix

D

Hazardous Materials Disclosure

D.1 Hazardous Materials Disclosure Table for IPB Products Certified as RoHS Compliant Under 2002/95/EC Without Mercury

The details provided in this appendix are to ensure that the product is compliant with the Peoples Republic of China (China) RoHS standards. The table below acknowledges the presences of small quantities of certain materials in the product, and is applicable to China RoHS only.

A label will be placed on each product to indicate the estimated “Environmentally Friendly Use Period” (EFUP). This is an estimate of the number of years that these substances would “not leak out or undergo abrupt change.” This product may contain replaceable sub-assemblies/components which have a shorter EFUP such as batteries and lamps. These components will be separately marked.

Please refer to the table on the next page.

DRPC-120-BTi Embedded System

| Part Name | Toxic or Hazardous Substances and Elements | | | | | |
|--------------------------------|--|-----------------------|-----------------------|------------------------------|--------------------------------|---------------------------------------|
| | Lead (Pb) | Mercury (Hg) | Cadmium (Cd) | Hexavalent Chromium (CR(VI)) | Polybrominated Biphenyls (PBB) | Polybrominated Diphenyl Ethers (PBDE) |
| Housing | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> |
| Display | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> |
| Printed Circuit Board | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> |
| Metal Fasteners | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> |
| Cable Assembly | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> |
| Fan Assembly | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> |
| Power Supply Assemblies | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> |
| Battery | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> | <input type="radio"/> |

O: This toxic or hazardous substance is contained in all of the homogeneous materials for the part is below the limit requirement in SJ/T11363-2006

X: This toxic or hazardous substance is contained in at least one of the homogeneous materials for this part is above the limit requirement in SJ/T11363-2006

此附件旨在确保本产品符合中国 RoHS 标准。以下表格标示此产品中某有毒物质的含量符合中国 RoHS 标准规定的限量要求。

本产品上会附有“环境友好使用期限”的标签，此期限是估算这些物质“不会有泄漏或突变”的年限。本产品可能包含有较短的环境友好使用期限的可替换元件，像是电池或灯管，这些元件将会单独标示出来。

| 部件名称 | 有毒有害物质或元素 | | | | | |
|--------|-----------|-----------|-----------|-----------------|---------------|---------------------|
| | 铅 (Pb) | 汞 (Hg) | 镉 (Cd) | 六价铬 (CR(VI)) | 多溴联苯 (PBB) | 多溴二苯 醚 (PBDE) |
| 壳体 | ○ | ○ | ○ | ○ | ○ | ○ |
| 显示 | ○ | ○ | ○ | ○ | ○ | ○ |
| 印刷电路板 | ○ | ○ | ○ | ○ | ○ | ○ |
| 金属螺帽 | ○ | ○ | ○ | ○ | ○ | ○ |
| 电缆组装 | ○ | ○ | ○ | ○ | ○ | ○ |
| 风扇组装 | ○ | ○ | ○ | ○ | ○ | ○ |
| 电力供应组装 | ○ | ○ | ○ | ○ | ○ | ○ |
| 电池 | ○ | ○ | ○ | ○ | ○ | ○ |

○: 表示该有毒有害物质在该部件所有物质材料中的含量均在 SJ/T11363-2006 标准规定的限量要求以下。
 X: 表示该有毒有害物质至少在该部件的某一均质材料中的含量超出 SJ/T11363-2006 标准规定的限量要求。